

UCM Series IP PBX Comparison Chart

Specifications					
	UCM6100 Series				UCM6510
Model	UCM6102	UCM6104	UCM6108	UCM6116	UCM6510
SIP Trunks	Up to 50				Unlimited
Users	Up to 500				Up to 2000
Concurrent Calls	30	45	60	60	200
Conference Bridges & Attendees	3 bridges, 25 attendees		6 bridges, 32 attendees		8 bridges, 64 attendees
Licensing Fees	None				
Zero Config	Yes				
FXO/FXS Ports	2 FXO 2 FXS	4 FXO 2 FXS	8 FXO 2 FXS	16 FXO 2 FXS	2FXO 2 FXS
E1/T1/J1 Interface	No				Yes - 1 RJ45 Port
Network Interface	Dual Gigabit with PoE+		1 Gigabit with PoE+		Dual Gigabit with PoE+ (3 rd Gigabit for Hot-standby clustering)
QoS	Layer 2 and Layer 3				
NAT Router	Yes	No			Yes
Clustering Port	No				Yes
Redundant Power Supply	No				Yes
RAM/Flash Memory	512 MB RAM, 4 GB Flash				1 GB RAM, 32 GB Flash
Processor	1GHz ARM Cortex 8				1GHz quad-core Cortex A9
Price	\$399	\$499	\$949	\$1,799	\$1,999