

Pressurized container: protect from sunlight and do not expose to

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety

Hand Protective Foam, 200 ml

Rust Loosener and Contact Spray 400 ml

data sheets (www.weicon.com) must be observed.

#### **Technical Datasheet**

Create Date: 16.11.2017 - Seite 1/

# **Rust Loosener and Contact Spray**



## 6-fold function

The six-fold function of Rust Loosener and Contact Spray makes it indispensible for repairs, maintenance and servicing. Thanks to its excellent creeping capacity, WEICON Rust Loosener and Contact Spray reaches even the smallest intermediate spaces. The 3-way spray valve makes it possible to work in any position (even overhead).

WEICON Rust Loosener and Contact Spray loosens rusted and stiff parts, screws, bolts, joints and hinges, dispels water from ignition systems, secures the function of mechanical parts and contacts, e.g. on distributor caps and spark plugs, sustainably protects against corrosion and oxidation, provides long-lasting lubrication to sliding surfaces, and cleans and cares for metal surfaces, mechanical parts and electrical systems.

## **Technical Data**

Odour	petroleum
Features	6-fold function
Storage stability	24 months
Colour	beige
Temperature resistance	-20 to +150 °C
ISSA-Code	53.402.09

### Processino

Shake can before use. Apply Rust Loosener and Contact Spray at approx. 5 cm distance from surface and let it work for approx. 30 seconds.

### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

Storage

Safety and health

Available sizes: 11150400

Accessories:

11850200

temperatures exceeding +50°C.

WEICON GmbH & Co. KG (Headquarters) Germany phone +49 (0) 251 9322 0 info@weicon.de

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon ae

WEICON South East Asia Pte Ltd Singapore phone (+65) 6710 7671 info@weicon.com.sg WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65 info@weicon.com.tr

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 WEICON Romania SRL Romania phone +40 (0) 3 65 730 763 office@weicon.com