Product data sheet Characteristics

NSYCRNG1210400D

Spacial CRNG plain door w/o mount.plate. H1200xW1000xD400 IP55 IK10 RAL7035





Main

Main		
Range	Spacial	
Product name	Spacial CRNG	ţ
Device application	Multi-purpose	3
Product or component type	Compact enclosure	ة ي پ
Enclosure nominal height	1200 mm	- CA-tig
Enclosure nominal width	1000 mm	i di
Enclosure nominal depth	400 mm	
Installation accessory type	Wall-mounting	
Device composition	Lock 1 Body 1 Door 2 Cable gland plate 2 bottom	o priniment
Door type	Plain	
Mounting plate description	Without mounting plate	9 9

Complementary

o o mpiorno mary		in the second se
Variant particularity	Single piece body	,
Number of doors	2 front face	
Door opening side	Reversible 120 °	
Lock type	3 points lock, 5 mm double-bar	" " T
Type of gland plate	Standard	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws	in i
Material	Steel for body	
Surface finish	Epoxy-polyester powder	
Colour	Grey RAL 7035	
Standards	IEC 62208	
Product certifications	CUL	,

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
	Product environmental	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Warranty period 18 months	