



Confidea T-CV

Confidea Tabletop Chairman Voting Unit



Description

The Confidea T-CV is Televic's tabletop chairman unit for discussion systems that include electronic voting. It combines a slim, contemporary design and excellent intelligibility with effortless ease of use. The units are equipped with a microphone On/Off or request-to-speak button and have two headphone outputs with a single volume control. Three voting buttons and an OLED information display facilitate voting and opinion polling during the meeting. The OLED display shows the result of a vote. The built-in RFID card reader can be used for authentication in case of electronic voting or identification in a free seating environment. From this unit, the chairman can

also control the overall system volume. Compared to the delegate version, this unit has additional controls and an extra OLED display. This display visualizes the voting start and -stop controls that this unit has. Other additional buttons are for priority and next-in-line controls. The units interconnect in daisy chain over Cat 5e Plixus® network cabling. The RJ45 connectors are hidden in the base of the unit and the cables are held in place by two notches in the unit housing.

Benefits

The Confidea T-CV is a *sleek and stylish solution* and can be set up in the blink of an eye. The

input and output connections are *auto-sensing and interchangeable*. As a result, installation is *easy, fast, and straightforward*, making it the ideal system for frequently changing environments. The removable microphone is *immune for mobile phone interference*, so delegates can leave their phones switched on during the meeting. The Confidea T-CV is backed by the Plixus® network with redundant cabling and hot swapping options to ensure *maximum reliability*. Finally, its shielded microphone is immune to mobile phone interference.

required. The following standard licenses are available:

CoCon Discussion	71.98.1101
CoCon Signage	71.98.1102
CoCon Voting	71.98.1104
CoCon Authentication	71.98.1105

Features

- Built-in high-quality loudspeaker which is automatically muted when the microphone is active, to prevent acoustic feedback
- Microphone On/Off or request-to-speak button with two signaling LEDs
- Two headphone outputs with single volume control
- Three voting buttons (+/0/-)
- Two OLED voting result displays
- RFID card reader
- Priority button
- Next-in-line button
- Start and stop voting from the unit
- Overall system volume control

Connectivity

- Screw-lock socket to connect a removable microphone.

D-MIC30SL	71.98.0053
D-MIC40SL	71.98.0054
D-MIC50SL	71.98.0055

- Two RJ 45 connectors for loop through cabling
- Two 3.5 mm stereo jack sockets for headphones
- Plixus-powered

Software

To fully configure, manage, and use the unit, Televic's CoCon management software is

Certifications

Region	Certification
Europe	CE

Specifications

Mechanical	
Material	PC/ABS
Color	Black Matt, RAL9011
Size (mm)	230 (w) × 130 (h) × 60 (d)
Size packed (mm)	250 (w) × 150 (h) × 90 (d)
Weight (g)	480
Weight packed (g)	620
Electrical	
Voltage	48 VDC
Consumption	4.5 W
Speaker Output	
Maximum output power	> 1 W
Frequency response	200-20,000 Hz
Dynamic range	> 90 dB
THD @ nominal level	< 0.1%
Load impedance	8 Ω
Headphone Output	
Maximum output	> 10 mW
Frequency response	22-22,000 Hz
Dynamic range	> 90 dB
THD @ nominal level	< 0.1%
Load impedance	16-32 Ω
Microphone Input	
Nominal input level	-54.7 dBV
Maximum input level	-24.6 dBV
Input impedance	1 kΩ
Dynamic range	> 93 dB
Frequency response	25-20,000 Hz
THD @ nominal level	< 0.1%

All information copyright **Televic Conference**,
2015. Version 1.0, October 2015

—
Leo Bekaertlaan 1 · 8870 Izegem · Belgium
Tel. +32 51 30 30 45
Fax +32 51 31 06 70
E-mail: conference@televic.com
Web: <http://www.televic-conference.com>
*Televic reserves the right to change this document
without notice.*



Confidea T-DV

Confidea Tabletop Delegate Voting Unit



Description

The Confidea T-DV is Televic's tabletop delegate unit for discussion systems that include electronic voting. It combines a slim, contemporary design and excellent intelligibility with effortless ease of use. The units are equipped with a microphone On/Off or request-to-speak button and have two headphone outputs with a single volume control. Three voting buttons and an OLED information display facilitate voting and opinion polling during the meeting. The OLED display shows the result of a vote. The built-in RFID card reader can be used for authentication in case of electronic voting or identification in a free seating environment. The chairman version of this unit

has additional controls. The units interconnect in daisy chain over Cat 5e Plixus® network cabling. The RJ45 connectors are hidden in the base of the unit and the cables are held in place by two notches in the unit housing.

Benefits

The Confidea T-DV is a *sleek and stylish solution* and can be set up in the blink of an eye. The input and output connections are *auto-sensing and interchangeable*. As a result, installation is *easy, fast, and straightforward*, making it the ideal system for frequently changing environments. The removable microphone is

immune for mobile phone interference, so delegates can leave their phones switched on during the meeting. The Confidea T-DV is backed by the Plixus® network with redundant cabling and hot swapping options to ensure *maximum reliability*. Finally, its shielded microphone is immune to mobile phone interference.

Features

- Built-in high-quality loudspeaker which is automatically muted when the microphone is active, to prevent acoustic feedback
- Microphone On/Off or request-to-speak push button with two signaling LEDs
- Two headphone outputs with single volume control
- Three voting buttons (+/0/-)
- OLED voting result display
- RFID card reader

Connectivity

- Screw-lock socket to connect a removable microphone.

D-MIC30SL	71.98.0053
D-MIC40SL	71.98.0054
D-MIC50SL	71.98.0055

- Two RJ 45 connectors for loop through cabling
- Two 3.5 mm stereo jack sockets for headphones
- Plixus-powered

Software

To fully configure, manage, and use the unit, Televic's CoCon management software is required. The following standard licenses are available:

CoCon Discussion	71.98.1101
CoCon Signage	71.98.1102
CoCon Voting	71.98.1104
CoCon Authentication	71.98.1105

Certifications

Region	Certification
Europe	CE

Specifications

Mechanical	
Material	PC/ABS
Color	Black Matt, RAL9011
Size (mm)	230 (w) × 130 (h) × 60 (d)
Size packed (mm)	250 (w) × 150 (h) × 90 (d)
Weight (g)	480
Weight packed (g)	620
Electrical	
Voltage	48 VDC
Consumption	4.5 W
Speaker Output	
Maximum output power	> 1 W
Frequency response	200-20,000 Hz
Dynamic range	> 90 dB
THD @ nominal level	< 0.1%
Load impedance	8 Ω
Headphone Output	
Maximum output	> 10 mW
Frequency response	22-22,000 Hz
Dynamic range	> 90 dB
THD @ nominal level	< 0.1%
Load impedance	16-32 Ω
Microphone Input	
Nominal input level	-54.7 dBV
Maximum input level	-24.6 dBV
Input impedance	1 kΩ
Dynamic range	> 93 dB
Frequency response	25-20,000 Hz
THD @ nominal level	< 0.1%

All information copyright **Televic Conference**, 2015. Version 1.0, October 2015

—
 Leo Bekaertlaan 1 · 8870 Izegem · Belgium
 Tel. +32 51 30 30 45
 Fax +32 51 31 06 70
 E-mail: conference@televic.com
 Web: <http://www.televic-conference.com>
Televic reserves the right to change this document without notice.