



## Confidea T-2D2I

Confidea Tabletop Double Delegate Interpretation Unit



### Description

The Confidea T-2D2I is Televic's tabletop delegate unit for discussion systems combined with simultaneous interpretation, fit for 2 delegates. It combines a slim, contemporary design and excellent intelligibility with effortless ease of use. The unit has 2 channel selectors and two headphone outputs with two volume controls. It allows both meeting delegates to speak, request-to-speak and listen to the speaker in his or her native language. Two OLED information displays indicate the selected channel number, the abbreviated channel language name in ISO format and a volume bar. The units interconnect in daisy chain over Cat 5e Plixus® network cabling. The RJ45 connectors are hidden in the

base of the unit and the cables are held in place by two notches in the unit housing.

### Benefits

The Confidea T-2D2I is a *sleek and stylish solution* and can be set up in the blink of an eye. The input and output connections are *auto-sensing and interchangeable*. As a result, installation is *easy, fast, and straightforward*, making it the ideal system for frequently changing environments. The removable microphone is *immune for mobile phone interference*, so delegates can leave their phones switched on during the meeting. The Confidea T-2D2I is backed by the Plixus® network with redundant





## Confidea T-D2I

Confidea Tabletop Delegate Discussion & Twin Interpretation Unit



### Description

The Confidea T-D2I is Televic's tabletop delegate unit for discussion systems combined with simultaneous interpretation, fit for 2 delegates. It combines a slim, contemporary design and excellent intelligibility with effortless ease of use. The unit has a single microphone button, 2 channel selectors and two headphone outputs with two volume controls. It allows both meeting delegates to speak, request-to-speak and listen to the speaker in his or her native language. Two OLED information displays indicate the selected channel number, the abbreviated channel language name in ISO format and a volume bar. The units interconnect in daisy chain over Cat 5e Plixus® network cabling. The RJ45 connectors are

hidden in the base of the unit and the cables are held in place by two notches in the unit housing.

### Benefits

The Confidea T-D2I is a sleek and stylish solution and can be set up in the blink of an eye. The input and output connections are auto-sensing and interchangeable. As a result, installation is easy, fast, and straightforward, making it the ideal system for frequently changing environments. The removable microphone is immune for mobile phone interference, so delegates can leave their phones switched on during the meeting. The Confidea T-D2I is backed by the Plixus® network with redundant cabling and hot swapping options to ensure maximum

reliability. Finally, its shielded microphone is immune to mobile phone interference.

## Features

- Built-in high-quality loudspeaker which is automatically muted when the microphone is active, to prevent acoustic feedback.
- Microphone On/Off or request-to-speak button with one signaling LED per button
- Two headphone outputs
- Two headphone volume adjustments
- Two Channel Up/Down adjustments
- Two OLED channel and volume information displays

## Connectivity & Accessories

- Screw-lock socket to connect a removable microphone.

<b>D-MIC30SL</b>	<b>71.98.0053</b>
<b>D-MIC40SL</b>	<b>71.98.0054</b>
<b>D-MIC50SL</b>	<b>71.98.0055</b>
<b>D-MIC70SL</b>	<b>71.98.0057</b>
<b>D-MIC40FF</b>	<b>71.98.0059</b>
<b>D-MIC40BC-C</b>	<b>71.98.0072</b>
<b>D-MIC40BC-H</b>	<b>71.98.0073</b>

- Two 3.5 mm stereo jack socket for headphones

<b>TEL152 Headphones</b>	<b>71.04.0154</b>
--------------------------	-------------------

## Software

To fully configure, manage, and use the unit, Televic's CoCon management software is required. The following standard licenses are available:

<b>CoCon Discussion</b>	<b>71.98.1101</b>
<b>CoCon Signage</b>	<b>71.98.1102</b>
<b>CoCon Interpretation</b>	<b>71.98.1107</b>

## Certifications

Region	Certification
Europe	CE

## Specifications

Mechanical	
Material	ABS
Color	Black
Size (mm)	250 (w) × 70 (h) × 80 (d)
Size packed (mm)	285 (w) × 85 (h) × 120 (d)
Weight (g)	880
Weight packed (g)	1000
Electrical	
Voltage	48 VDC
Consumption	< 3.5 W
Speaker Output	
Maximum output power	> 1 W
Frequency response	200-20,000 Hz
Dynamic range	> 90 dB
THD @ nominal level	< 0.1%
Load impedance	8 Ω
Headphone Output	
Maximum output	> 10 mW
Frequency response	22-22,000 Hz
Dynamic range	> 90 dB
THD @ nominal level	< 0.1%
Load impedance	16-32 Ω
Microphone Input	
Nominal input level	-54.7 dBV
Maximum input level	-24.6 dBV
Input impedance	1 kΩ
Dynamic range	> 93 dB
Frequency response	25-20,000 Hz
THD @ nominal level	< 0.1%

All information copyright **Televic Conference**, 2017. Version 1.0, March 2017

—  
 Leo Bekaertlaan 1 · 8870 Izegem · Belgium  
 Tel. +32 51 30 30 45  
 Fax +32 51 31 06 70  
 E-mail: [conference@televic.com](mailto:conference@televic.com)  
 Web: <http://www.televic-conference.com>  
*Televic reserves the right to change this document without notice.*