UNI-T

: UT-211 IV õ õ õ 2 2 2 2 3 3 А. В. C. D. 3 E. 3 3 4 2. A. $\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}$ В. 4õ C. 4 D. Δ E. F. $\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}}\;\tilde{\mathtt{o}}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;\tilde{\mathtt{o}}\;$ 4 4 A. $\tilde{o}\ \tilde{o}\ \dots\dots\dots$ 4 В. $..\tilde{0}\ \tilde{0}\ \dots \dots$ 4 Δ UT-211 (3 ¾-») . 3999. 600 . 60 30 , ₫. 3 (NEDA 1604, 6F22 009P) IEC61010, 2, II. 600 , III. 300 , II: Ш

III:

UNI-T

<u>UNI-T</u> : UT-

211

• , . . .

•

• , , ,


| = | | | |
|---------------|------|------|---|
| | (AC) | (DC) | |
| ÷ | | | |
| 4 | | | |
| CE | | | |
| $lack \Delta$ | • | | - |
| | | | |

(. 1)


1. ,

.

2. 3. 4.



| | 1 |
|---------|--------|
| Hz/% | |
| HOLD | 1101.5 |
| 0 | HOLD. |
| (POWER) | |



| 1 | Hz / % | |
|---|--------|--|
| 2 | HOLD | |
| 3 | 9==+ | |


| 4 | AC | |
|---|------------|----------|
| 5 | DC | |
| 6 | OL | |
| 7 | Auto | , - |
| 8 | 盘 | ▲ |
| | , k , M | : , |
| | V | V: , |
| 9 | Α | |
| | Hz | |
| | % | : |

«OL».

A. (. 3)

Δ

600 , ,



1. **V**,

2. COM. 1,4 ±1,4 ,

·

• 10

: UT-211

UNI-T 0,2 В. 4) 0,5 OL, (>1 000 000 D. Hz% 1. 2. Hz% 3. 4. 4. 4,0 E. HOLD, HOLD 5) HOLD, 30 (60) HOLD, HOLD 000 red 400 Auto : 3999, 3 ¾ : OL 5. 2-3 1. COM. 2. + 5% : 0° . +40° (32°F . +104°F) : -10° . +50° (14°F . +122°F) : ≤75% 0° . 30°

0,1

3

UNI-T : UT-

<u>211</u>

: ≤ 50% : ≤ 2000 : ≤ 10000 30° . 40°

9 6F22, NEDA 1604, 006P 盘

: 210 : 75,6 30 (300 (

: IEC61010:

II -600 , III -

300 , ∶**(€**

: $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$: ≤ 75%

| 1 | 1 | ±(1%+3) | 600 | |
|-------|------|---------|-----|--|
| F. | | | | |
| | | | | |
| | | | | |
| 99,9% | 0,1% | | 600 | |

A.

| 4 | 1 | | |
|-----|-----|-----------|-----|
| 40 | 10 | ±(0,8%+1) | 600 |
| 400 | 100 |] | 600 |
| 600 | 1 | ±(1%+3) | |

10

≥1,4

В.

| 4 | 1 | | |
|-----|-----|-----------|-----|
| 40 | 10 | ±(1,2%+5) | 600 |
| 400 | 100 | | 600 |
| 600 | 1 | ±(1,5%+5) | |

10

. 400

≥1,4

| 40 | 10 | 0,4 ≤ ≤20 : ±(3,0%+8) |
|-----|-----|-----------------------|
| 40 | | >20 : ±(2,0%+8) |
| 400 | 100 | ≤200 : ±(1,5%+5) |
| 400 | | >290 : ±(1,5%+50) |

:50 .60

≥0,4


D.

| 400 | 0,1 | ±(1,2%+2) + | |
|-----|-----|-------------|-----|
| 4 | 1 | | |
| 40 | 10 | ±(1,0%+2) | 600 |
| 400 | 100 | | |
| 4 | 1 | ±(1,2%+2) | |
| 40 | 10 | ±(1.5%+2) | |

E.

6)

В.



«Ξ±».

1. 2.

3. 4. 5. 9 (NEDA1604, 6F22 006P).