

KL-21C

High Precision Fiber Cleaver





Traditional bench top design



48000 Blade life



All-in-1 Universal fiber holder



≤0.5° Cleaved angle



Auto Fiber Offcut Bin

\bigcirc

Characteristics Description

- Traditional bench top design, simple and easy to use
- Typical Cleave Angel 0.5°
- Applicable to 250µm, 900µm, 3.0mm fiber cable and flat cable

- Blade life 48,000 cleaves
- Auto Fiber Offcut Bin
- Large capacity waste fiber bin, automatic collecting, reduce pollution and scratches



Silicone pressure pad can effectively hold down the fiber.



Applicable to 250µm, 900µm, 3.0mm fiber cable and flat cable.




Tungsten steel refined blade Wear resistance, high hardness, corrosion resistance.



Auto Fiber Offcut Bin.



All-in-1 Universal Fiber Holder








Special carrying case

The card slot in the box is designed to effectively protect the cleaver body from damage.





Product Specifications

Fiber Meterial	Silica glass
Cladding Diameter	125 µm
Cleaved Length	Single fiber: 8~20mm / Ribbon fiber: 10mm
Applicable Fiber Cable	Single fiber: 250µm, 900µm, 3.0mm;
	Fiber cable and flat cable Ribbon fiber: 2 to 12 ribbon fiber cable
Typical Cleaved Angle	Less than 0.5° ★①
Typical Blade Life	Total 48,000 fiber cleaves (replaceable) ★②
Off-cut Collector	Pre-fitted
Type of Offcut Bin	Auto
Auto Return	Pre-fitted
Dimension	83W *77D*63H(mm)
Weight	355g

- ★① Cleaved angel may vary depending on the operating environment.
- \bigstar Blade life is not guaranteed. It may vary depending on the operating environment.

⇔ Product Display









Contact us

Nanjing Jilong Optical Communication Co., Ltd

Address: 12F, Changfeng Technology Building 2, NO.14 Xinghuo Rd, Pukou District Nanjing City 210032, China

Tel: +86-025-58880885 Mail: info@jilongot.com Web: www.JILONGOT.com



Focus on official website for more