



SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/1000V	$\pm (0.8\%+8)$
AC Voltage	4V/40V/400V/750V	$\pm (1\%+15)$
DC Current	400 μ A /4000 μ A/40mA/400mA/4A/10A	$\pm (1\%+8)$
AC Current	400 μ A/4000 μ A/40mA/400mA/4A/10A	$\pm (1.5\%+8)$
Resistance	400 Ω / 4k Ω /40k Ω /400k Ω /4M Ω / 40M Ω	$\pm ?\%+5)$
Capacitance	40nF /400nF/4 μ F/40 μ F/100 μ F	$\pm ?\%+(3\%+8)$
Frequency	10Hz~10MHz	$\pm (0.1\%+3)$
Vertical Accuracy		$\pm ?\%+1)$
Input Sensitivity	20mV/div-500V/div (1-2-5)	?img src="Images/TICK.GIF" width="17" height="9" border="0">
Horizontal Accuracy		$\pm (0.01\%+1)$
Timebase Range	100ns/div-5s/div (1-2-5)	?img src="Images/TICK.GIF" width="17" height="9" border="0">
Bandwidth	8MHz	✓
Display Resolution	160X160	✓
Real-Time Sample Rate	40MSa/s	✓
Duty Cycle	0.1%~99.9%	✓
Special Functions	?/font>	?/font>
Diode		✓
Continuity Buzzer		✓
Display	160x160 Monochrome	✓
Trigger Types	Free Run / Normal / Single Shot	✓
Memory	10 screens and setups	✓
Contrast and Bright Setup		✓
Input Impedance For DC Voltage Measurement	Around 10M Ω	✓
Sleep Mode		✓
Low Battery Display		✓
Display Backlight	EL	✓

USB		✓
Max.Display	3999	✓

GENERAL CHARACTERISTICS

Power	1.5V Battery (R6) x 4
LCD Size	60 x 60 mm
Product Color	Red and Grey
Product Net Weight	498g
Product Size	200 x100 x 48 mm
Standard Accessories	Test Lead , Battery, English Manual ,Alligator Clip, USB Interface Cable, Software, Power Adapter
Optional Accessories*	Scope Probe, BNC Probe
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	20 pcs
Standard Carton Measurement	542 x 376 x 388 mm (0.079 CBM Per Standard Carton)
Standard Carton Gross Weight	25kg