



MBR1020 THRU MBR1060

肖特基二极管 Schottky Rectifier


■特征 Features

- I_o 10A
- V_{RRM} 20V-60V
- 耐正向浪涌电流能力高
High surge current capability
- 封装: 模压塑料
Cases: Molded plastic

■用途 Applications

- 整流用 Rectifier

■外形尺寸和印记 Outline Dimensions and Mark



■极限值（绝对最大额定值）

Limiting Values (Absolute Maximum Rating)

参数名称 Item	符号 Symbol	单位 Unit	测试条件 Test Conditions	MBR				
				1020	1030	1040	1050	1060
反向重复峰值电压 Repetitive Peak Reverse Voltage	V _{RRM}	V		20	30	40	50	60
正向平均电流 Average Forward Current	I _{F(AV)}	A	正弦半波 60Hz, 电阻负载, T _c (Fig.1) 60HZ Half-sine wave, Resistance load, T _c (Fig.1)	10.0				
正向（不重复）浪涌电流 Surge(Non-repetitive)Forward Current	I _{FSM}	A	正弦半波 60Hz, 一个周期, T _a =25℃ 60Hz Half-sine wave ,1 cycle , T _a =25℃	250				
结温 Junction Temperature	T _J	℃		-55~+125			-55~+150	
储存温度 Storage Temperature	T _{STG}	℃		-55 ~ +150				

■电特性（ $T_a=25^{\circ}C$ 除非另有规定）

Electrical Characteristics ($T_a=25^{\circ}C$ Unless otherwise specified)

参数名称 Item	符号 Symbol	单位 Unit	测试条件 Test Condition		MBR				
					1020	1030	1040	1050	1060
正向峰值电压 Peak Forward Voltage	V _F	V	I _F =10.0A		0.55			0.70	
反向漏电流 Peak Reverse Current	I _{RRM1}	mA	V _{RM} =V _{RRM}	T _a =25℃	0.2				
	T _a =100℃			50					
热阻(典型) Thermal Resistance(Typical)	R _{θJ-C}	℃/W	结和壳之间 Between junction and case		7.0 ¹⁾				

备注: Notes:

¹⁾ 热电阻从结到本体,每管脚到散热片的尺寸为 2"×3"×0.25 的铝板

Thermal resistance from junction to case per leg with heat-sink size of 2"×3"×0.25" AL-plate

■特性曲线（典型） Characteristics(Typical)

图1: 正向电流降额曲线
FIG.1: FORWARD CURRENT DERATING CURVE




图2: 最大正向浪涌冲击耐受力
FIG.2: MAXIMUM NON-REPETITIVE FORWARD URGE CURRENT




图3: 典型正向特性曲线
FIG.3: TYPICAL FORWARD CHARACTERISTICS




图4: 典型反向特性曲线
FIG.4: TYPICAL REVERSE CHARACTERISTICS

