



# RED RUBBER GREASE

## GENERAL DESCRIPTION:

### NON-MELT GELLED VEGETABLE OIL

A top quality lubricating grease manufactured from best quality vegetable oil and thickened with non-soap bentonite, together with corrosion and oxidation inhibitors.

The grease has good mechanical stability and is compatible with natural and synthetic rubbers. It is resistant to hydrocarbons and most chemicals. Eliminates rubber swelling.

## APPLICATION:

It is designed for use on automotive brake assemblies, rubber components, and hydraulic components. Because of its resistance to lubricating oil it is suitable for gland packing and seals.

## TECHNICAL DETAILS:

### TYPICAL TEST DATA:

Base	Gelled vegetable oil.
Appearance	Red grease.
Texture	Smooth
NLGI Grade	No. 2
Drop Point	None-Infusible
Working temperature range	-40°C to 110°C
Water Solubility	Insoluble

## PACKING DETAILS:

Available in 0.5kg and 5kg

**Molyslip Atlantic Ltd.**  
**A1 Danebrook Court, Langford Lane, Kidlington, Oxon, OX 5 1LQ**  
**Tel: 01865 370 032, Fax: 01865 372 030**  
**E-mail: [enquiries@molyslip.co.uk](mailto:enquiries@molyslip.co.uk)**