

Disclean 25 I

Product Group: 651

Product number: 571687

General description

Disclean is a water based blend of inhibited acids, surfactants and emulsifying agents. Disclean removes the heavy tenacious deposits which collect in fuel and lube oil centrifugal separators, and it is extremely effective in removing these deposits without the necessity of separating the discs from the stack.

Features

- Acid based product containing surfactants
- Does not contain nonyl phenol ethoxylates or other estrogenic compounds
- Non-flammable
- Remove heavy tenacious deposits
- Cleans down to metal surfaces
- Leaves no film or residue
- Reduces down time
- Allows cleaning of disc without dismantling of disc stacks
- Cleans all types of separator discs
- Approved by Marinfloc AB for use in engine rooms

It is recommended that this product is not used on zinc, tin, galvanised surfaces or anodised aluminium.

The Uitor Chemical Cleaning Unit (Product no. 664 737189) can be used for soak cleaning of disc stacks.

Ordering information

Product number	Product name
571687	DISCLEAN 25 LTR

Directions for use

Disclean may be used neat or diluted down to 20% by volume with fresh water, depending on the severity of contamination, availability of heat and time to complete cleaning operation. The higher the concentration the more efficient the cleaning action.

The time for a cleaning operation will vary from 30 minutes to maximum 2 hours depending on the above factors. Faster and more efficient cleaning can be accomplished by heating to a maximum temperature of 60 °C.

After the unit or parts have been satisfactorily cleaned, they shall be rinsed thoroughly with fresh water to remove all traces of contamination and Disclean.

Method of cleaning Separators can be cleaned by:

1. Removing the separator disc stack and soaking in a solution of Disclean. Circulating the solution and heating will enhance the cleaning.
 2. Removing the separator discs and dismantling stack, then soaking discs in Disclean. Circulating and heating the solution will enhance the cleaning. Discs can be sprayed if soaking tank is not available.
-
-

Documentation

SDS

- [DISCLEAN 25 LTR](#)
-

Further Technical Data

Form Liquid

Appearance Light yellow

Density 1,3

pH, in 1% sol. 2

Not Compatible Corrosive to mild steel, cast iron, aluminium and alloys, brass, tin or galvanised material.