



\* not present on all models

## FEATURES OF HAND-HELD DRILLING MACHINES

The EIBENSTOCK high performance hand-held drills are great for drilling steel, aluminium, plastic, hard and soft wood. All machines are robust and powerful for continuous use and high operational reliability.

EIBENSTOCK drilling machines are mainly used in the metalworking and assembly industries as well as steel construction, machinery, plant and vehicles renovation and the carpentry and wood industries.



## Hand-held drilling machine EHB 32/4.2



Ø 32  
in steel

4

## Magnetic drill rig B 32.1



Max. drilling diameter:  
twist drill 32 mm  
core drill 100 mm  
taper M 20

### Powerful model

#### APPLICATION:

- Hand-held or stand mounted drilling in wood, aluminium, steel
- Screwing and tapping (EHB 32/2.2 R R/L forward reverse and torque control)
- As a driving motor
- Metal and timber construction, machine, plant and vehicle construction

#### FEATURES:

- Soft start, temperature control and over current cut-off (EHB 32/2.2 R R/L) – protection of the machine
- Torque control, speed regulation and constant speed (EHB 32/2.2 R R/L) – optimal adjustment to material and drilling diameter
- Mechanical safety clutch – protection of the user
- Morse taper connection – versatile spindle connection

### Strong magnetic connection for safe working

#### APPLICATION:

- Safety drilling and milling overhead and on sloping steel surfaces
- Metal and timber construction, machine, plant and vehicle construction

#### FEATURES:

- Connecting screw drill stand/drilling machine for precise guiding especially for core hole drilling – protection against turning
- Base with high magnetic force – safe working
- Robust design with solid, durable dovetail guide
- Suitable for the EIBENSTOCK EHB 32/2.2 R R/L and EHB 32/4.2 models

SPECIFICATIONS	EHB 32/4.2
Power input	1700 W
Rated voltage	230 V ~
Rated speed	110/175/245/385 rpm
No-load speed	215/330/460/680 rpm
Max. drilling-Ø wood/alu/steel	100/60/32 mm
Reversible	no
Spindle connection	MT 3
Collar diameter	65 mm
Weight	6.9 kg
Order no.	0154A000

Supplied in a box  
incl. drill drift MT 3

SPECIFICATIONS	B 32.1
Power input	110 W
Rated voltage	230 V ~
Magnetic holding force	16000 N
Size of magnet	220 x 110 mm
Collar diameter	65 mm
Hub	180 mm
Height	409 mm
Socket outlet	max. 16 A
Weight	17.0 kg
Order no.	09507000









Supplied in a case incl. safety belt,  
weldon mounting shank MT 3  
and assembly tools





## Drilling ACCESSORIES

### FOR HAND-HELD DRILLING MACHINES

	<p>1 Magnetic drill rig B 32.1 for EHB 32/2.2 R R/L and EHB 32/4.2</p>	<p>09507000</p>
	<p>2 Weldon mounting shank MK 3 - Ø 19 mm</p>	<p>33125000</p>
	<p>3 Taper mandrel B 18/MT 2 B 18/MT 3</p>	<p>33112000 33122000</p>
	<p>4 Quick action drill chuck ½" x 20 Ø 13 mm B 16 Ø 13 mm</p>	<p>33433000 33431000</p>
	<p>5 Scroll chuck B 18 Ø 16 mm</p>	<p>33342000</p>
	<p>6 Adapter MT 2 male - M 14 female MT 3 male - M 14 female</p>	<p>33113000 33123000</p>
	<p>7 Drill chuck key 16</p>	<p>33540000</p>
	<p>8 Plastic case for EHB 16, EHB 20/2.4</p>	<p>37332000</p>