



* not present on all models

FEATURES OF HAND-HELD DRILLING MACHINES

The EIBENSTOCK high performance hand-held drills are great for drilling steel, aluminium, plastic, hard and soft wood. All machines are robust and powerful for continuous use and high operational reliability.

EIBENSTOCK drilling machines are mainly used in the metalworking and assembly industries as well as steel construction, machinery, plant and vehicles renovation and the carpentry and wood industries.



Hand-held drilling machine EHB 16/2.4 S R/L



Ø 20
in steel

↔ 2

Compact model

APPLICATION:

- Drilling and screwing of wood, aluminium, steel
- Mobile for easy transport to site
- Metal and timber construction

FEATURES:

- Soft start speed control – precise drilling/screwing
- Reversible – easily remove of the drill bit from holes and easily screw in and remove screws
- High torque gearbox – powerful drilling
- Adjustable handle with aluminium clamp – allows adaptation to the application and working position
- Long front handle allowing for easy handling at high torque and optimal power transmission
- Spade handle – optimal power transmission

SPECIFICATIONS	EHB 16/2.4 S R/L
Power input	1150 W
Rated voltage	230 V ~
Rated speed	0-430/0-760 rpm
No-load speed	0-700/0-1200 rpm
Max. drilling-Ø wood/alu/steel	65/28/20 mm*
Reversible	yes
Spindle connection	5/8" x 16 UN
Collar diameter	43 mm
Weight	3.5 kg
Order no.	0122H000

Supplied in a box
incl. drill chuck key

* Drill with shaft 16 mm



Hand-held drilling machine EHB 32/2.2 R R/L



Reversible

Ø 32
in steel

↔ 2

Powerful model

APPLICATION:

- Hand-held or stand mounted drilling in wood, aluminium, steel
- Screwing and tapping (EHB 32/2.2 R R/L forward reverse and torque control)
- As a driving motor
- Metal and timber construction, machine, plant and vehicle construction

FEATURES:

- Soft start, temperature control and over current cut-off (EHB 32/2.2 R R/L) – protection of the machine
- Torque control, speed regulation and constant speed (EHB 32/2.2 R R/L) – optimal adjustment to material and drilling diameter
- Mechanical safety clutch – protection of the user
- Morse taper connection – versatile spindle connection

SPECIFICATIONS	EHB 32/2.2 R R/L
Power input	1800 W
Rated voltage	230 V ~
Rated- /No-load speed	60-140/200-470 rpm
Max. drilling-Ø wood/alu/steel	100/60/32 mm
Reversible	yes
Spindle connection	MT 3
Collar diameter	65 mm
Weight	6.4 kg
Order no.	0152H000









Supplied in a box
incl. drill drift MT 3





Drilling ACCESSORIES

FOR HAND-HELD DRILLING MACHINES

	<p>1 Magnetic drill rig B 32.1 for EHB 32/2.2 R R/L and EHB 32/4.2</p>	<p>09507000</p>
	<p>2 Weldon mounting shank MK 3 - Ø 19 mm</p>	<p>33125000</p>
	<p>3 Taper mandrel B 18/MT 2 B 18/MT 3</p>	<p>33112000 33122000</p>
	<p>4 Quick action drill chuck ½" x 20 Ø 13 mm B 16 Ø 13 mm</p>	<p>33433000 33431000</p>
	<p>5 Scroll chuck B 18 Ø 16 mm</p>	<p>33342000</p>
	<p>6 Adapter MT 2 male - M 14 female MT 3 male - M 14 female</p>	<p>33113000 33123000</p>
	<p>7 Drill chuck key 16</p>	<p>33540000</p>
	<p>8 Plastic case for EHB 16, EHB 20/2.4</p>	<p>37332000</p>