

AXIS P1378-LE Network Camera

Excellent details in 4K for the great outdoors

With a robust design, AXIS P1378-LE offers excellent details in 4K resolution and can withstand extreme temperatures ranging from -40 °C to 60 °C (-40 °F to 140 °F). For extra protection an optional weathershield is available. It delivers excellent details in challenging or low light and includes Axis OptimizedIR for surveillance in pitch darkness. Designed as a deterrent, it includes electronic image stabilization, shock detection, tampering alarm and video streaming indicator. Axis Zipstream supporting H.264/H.265 provides exceptional savings on bandwidth and storage. Plus, with CS mount and support for motorized i-CS, you can easily change lens to meet your requirements.

- > **4K resolution**
- > **OptimizedIR and Forensic WDR**
- > **Signed firmware and secure boot**
- > **Electronic image stabilization**
- > **Zipstream supporting H.264 and H.265**



AXIS P1378-LE Network Camera

| | | | |
|-----------------------------|--|--|---|
| Camera | | Onscreen controls | Electronic image stabilization Day/night shift Defogging Wide dynamic range |
| Image sensor | 1/1.8" progressive scan RGB CMOS | Event triggers | Analytics, shock detection, open casing, edge storage events, supervised external input, audio level, time scheduled MQTT subscribe |
| Lens | IR corrected, CS-mount lens, P-Iris Varifocal 3.9–10 mm, F1.5 With IK10 protection in front window Horizontal field of view: 115°–45° Vertical field of view: 61°–25° Without IK10 protection in front window Horizontal field of view: 119°–45° Vertical field of view: 62°–25° | Event actions | File upload: FTP, SFTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS and TCP External output activation Video recording to edge storage, Play audio clip Pre- and post-alarm video buffering PTZ preset, Guard tour, Overlay text Day/Night switching, Status LED activation MQTT publish Send SNMP trap |
| Day and night | Automatically removable infrared-cut filter | Built-in installation aids | Focus assistant, pixel counter, remote back focus, autorotation, remote focus and zoom and with optional i-CS lens. |
| Minimum illumination | 4K 25/30 fps with Forensic WDR and Lightfinder: Color: 0.15 lux, at 50 IRE F1.5 B/W: 0.03 lux, at 50 IRE F1.5 0 lux with IR illumination on | Analytics | |
| Shutter speed | 1/8500 s to 1/5 s | AXIS Object Analytics | Object classes: humans, vehicles Features: line crossing, object in area, crossline counting ^{BETA} , time in area ^{BETA} Up to 10 scenarios Metadata visualized with trajectories, color-coded bounding boxes and tables Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event |
| System on chip (SoC) | | Metadata | Object data: Classes: humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates Confidence, position Event data: Producer reference, scenarios, trigger conditions |
| Model | ARTPEC-7 | Applications | Included AXIS Object Analytics, AXIS Video Motion Detection, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, active tampering alarm, audio detection Supported AXIS Live Privacy Shield, AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap |
| Memory | 2 GB RAM, 512 MB Flash | Cybersecurity | |
| Compute capabilities | Machine learning processing unit (MLPU) | Edge security | Software: Signed firmware, brute force delay protection, digest authentication, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Secure boot |
| Video | | Network security | IEEE 802.1X (EAP-TLS), HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, IP address filtering |
| Video compression | H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Motion JPEG Controllable frame rate and bandwidth | Documentation | <i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity |
| Resolution | 3840x2160 (4K) to 160x90 | General | |
| Frame rate | 25/30 fps (50/60 Hz) | Casing | IP66-, IP67- and NEMA 4X-rated, IK10 impact-resistant polymer enclosure with aluminium base and intrusion alarm switch Weathershield with black anti-glare coating Color: White NCS S 1002-B |
| Video streaming | Multiple, individually configurable streams in H.264, H.265, and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Low latency mode Video streaming indicator | Sustainability | PVC free |
| Multi-view streaming | Up to 8 individually cropped out view areas | Power | 12–28 V DC, max 25.5 W (incl. front heater), typical 11.1 W Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 4, max 25.5 W (incl. front heater), typical 11.7 W Power redundancy |
| Image settings | Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, local contrast, tone mapping, compression, orientation: auto, 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, dynamic text and image overlay, privacy masks, defogging, electronic image stabilization, barrel distortion correction, scene profiles: forensic, vivid, traffic overview | Connectors | RJ45 10BASE-T/100BASE-TX/1000BASE-T I/O: 6-pin 2.5 mm terminal block, for 2 supervised alarm inputs and 2 outputs RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block DC input, terminal block 3.5 mm mic/line in, 3.5 mm line out |
| Pan/Tilt/Zoom | Digital PTZ Uploadable PTZ driver (Pelco D pre-installed) | System integration | |
| Audio | | Application Programming Interface | |
| Audio streaming | Two-way, full duplex | Open API for software integration, including VAPIX® and AXIS Camera Application Platform, specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection One-click cloud connection ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S and ONVIF® Profile T, specification at onvif.org | |
| Audio encoding | AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 8/16/32/48 kHz Configurable bit rate | | |
| Audio input/output | External microphone input, line input, digital input with ring power, line output, automatic gain control | | |
| Network | | | |
| Network protocols | IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS, HTTP/2, TLS, QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SFTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf) | | |

| | |
|-----------------------------|--|
| | i-CS connector (compatible with P-Iris and DC-iris) |
| IR illumination | Optimized IR with power-efficient, long-life 850 nm IR LEDs Range 50 m (164 ft) or more, depending on the scene |
| Storage | Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com |
| Operating conditions | -40 °C to 60 °C (-40 °F to 140 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Humidity 10–100% RH (condensing) Wind load (sustained): 55 m/s (123 mph) |
| Storage conditions | -40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing) |
| Approvals | EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 60950-22, CAN/CSA-C22.2 No. 60950-22, IEC 62471, IS 13252 Environment IEC/EN 60529 IP66/IP67, NEMA 250 Type 4X, NEMA TS 2 (2.2.7–2.2.9), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 62262 IK10 |

| | |
|----------------------------------|--|
| | Network NIST SP500-267 |
| Dimensions | 404 x 159 x 168 mm (15.9 x 6.3 x 6.6 in) |
| Weight | 2.4 kg (5.3 lb) |
| Included accessories | Installation guide, Windows® decoder 1-user license, wall mount bracket, sunshield, connector kit IK10 tool Torx® T20 screw driver, Torx® T30 screw bit AXIS P13 Weathershield Kit A Pre-mounted AXIS Fixed Box IR Illuminator Kit A |
| Optional lenses | Lens CS 4–10 mm F0.9 P-Iris Lens i-CS 3.9–10 mm F1.5 8 MP Lens i-CS 9–50 mm F1.5 8 MP |
| Optional accessories | Axis mounts, Axis lenses, Axis midspans, Axis microphones AXIS P13 Weathershield Extension A AXIS T8355 Digital Microphone AXIS T99A10 Positioning Unit 24 V AC/DC For more accessories, see axis.com |
| Video management software | AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available at axis.com/vms |
| Languages | English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese |
| Warranty | 5-year warranty, see axis.com/warranty |