

# AXIS TU6004-E Cable

## Indoor- and outdoor cable

This flexible and robust indoor/outdoor cable is compatible with AXIS F91 main units, AXIS F21 sensor units, AXIS F4105-LRE Dome Sensor, and AXIS F7225-RE Pinhole Sensor. With a 40 mm (1.6 in) bending radius, this high-speed data cable offers a high bandwidth capability to minimize latency between the sensor unit and main unit. It comes in 3 different lengths: 1 m (3 ft), 8 m (26 ft) and 30 m (98 ft).

- > **Indoor and outdoor rated**
- > **40 mm (1.6 in) bending radius**
- > **1 m (3 ft), 8 m (26 ft), 30 m (98 ft)**
- > **1 m (3 ft) and 8 m (26 ft) cables are sold in pack of 1 and 4**
- > **30 m (98 ft) cable is sold in pack of 1**



## AXIS TU6004-E Cable

General	
<b>Power</b>	Impedance: 50 Ohms
<b>Frequency</b>	0–3 GHz
<b>Connectors</b>	SMA FAKRA
<b>Operating conditions</b>	–40 °C to 75 °C (–40 °F to 167 °F) Humidity 10–85% RH (non-condensing)
<b>Approvals</b>	UL CL2 Sunlight Resistant E335585-T
<b>Dimensions</b>	Color: black Length: 1 m (3 ft), 8 m (26 ft) and 30 m (98 ft) Ø 5 ±0.1 mm (0.2 in) Maximum length of interconnected cables: ≤than 30 m (98 ft)
	Bend radius: 40 mm (1.6 in)
<b>Weight</b>	1 m (3 ft): 40 g (0.09 lb) 8 m (26 ft): 300 g (0.66 lb) 30 m (98 ft): 1140 g (2.51 lb)
<b>Compatible products</b>	AXIS F91 main units, AXIS F21 sensor units, AXIS F4105-LRE Dome Sensor, AXIS F7225-RE Pinhole Sensor
<b>Optional accessories</b>	AXIS TU6003 Connector Kit FAKRA
<b>Warranty</b>	3-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>
	Environmental responsibility: <a href="https://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a>