

Somi Tape Industrial Limited

广州市顺固美胶粘带有限公司

Technical Data Sheet
技术数据表

Updated: May 2017

Product Name
品名

SH903 Slip-Resistant Tape

Product Picture
产品图片



Product Description
产品描述

SH903 consists of abrasive particles bonded by a tough, durable polymer to a dimensionally stable plastic film. The reverse side is coated with a pressure-sensitive adhesive covered by a removable protective liner.

Physical Properties
物理特性

Tape Color 胶带颜色	Black
Width 宽度	50 mm
Standard Roll Length 标准长度	18 m
Applied Thickness 应用厚度	0.7-0.8 mm
Adhesive Type 胶水类型	Acrylic
Base Material 基材	0.05mm PET
Release Liner 离型纸	White Silicon Paper
Surface Sand 砂面	Aluminium oxide 金刚砂
Surface Granularity 目数	60#
Applied Weight 重量	850 g/m ²

Performance Characteristics 性能特性	Peel Adhesion 180° 剥离强度	Immediate: 27N/25mm 24 Hour: 31N/25mm
	Coefficient of Friction 摩擦系数	R13(>0.70)
	Dynamic Coefficient of Friction 动摩擦系数	0.75 Dry Leather / 1.04 Wet Rubber
	Static Coefficient of Friction 静摩擦系数	1.03 Dry Leather / 1.32 Wet Rubber
	Application Temperature 使用温度	-30~80 °C

Product Applications
产品应用

Farm Machinery; Construction Equipment, Forklifts, Cherry pickers; Steps, stairs, and platforms; Recreational Vehicles, Snowmobiles, ATVs, Garden tractors, Lawn mowers; Wet and oily areas; Loading docks, Cold storage, Catwalks, Platform/ramps; Ladders, Step stools, Scaffolds; Airplane decks/cargo holds, Trains, Semi-trailers, Buses, Ships decks; Food service area.

Storage
存储

Store under normal conditions of 16°C to 27°C and 40% to 60% Relative Humidity in the original carton.

Shelf Life
保质期

To obtain best performance, use this product within 24 months from date of manufacture.

Somi Tape Industrial Limited

9th, Wang Gang Industrial Zone,
 Longdong, Guangzhou 510520,
 Guangdong province, China

TEL: +86-20-87710841

FAX: +86-20-37250876

Web: www.somitape.com

Email: somi@somitape.com