



LCD Video Wall

Improved customer experience

Create virtually seamless video walls thanks to the thin bezels of Prestigio Solutions devices, measuring just 3.5 mm. Equipped with high contrast ratio along with wide viewing angles, these video wall displays deliver an impressive experience. And the modern, slim design allows the display to blend into any business environment.

Bright FHD non-glare picture round-the-clock

Experience brilliant image presentation with an impressive brightness empowering your business to deliver clear information 24/7. The display's non-glare panels provide excellent visibility regardless of ambient light, helping to ensure critical information is always visible.

Portrait & landscape orientation

The ability to use video wall in portrait and landscape orientation allows you to conveniently place devices in the interior and create personalized advertising campaigns which perfectly suits to the environment.

Nearly invisible 3.5 mm dual bezel

The Prestigio Solutions 55" LCD Video Wall features a sufficiently thin 3,5 mm bezel-to-bezel depth — that enables content to be delivered as one virtually seamless image. And 10-bit color depth provides smooth gradations and improved realism in photography and video content.

LCD VIDEO WALL

PSIW55N0U0

Prestigio Solutions 55" LCD Video Wall with 3.5 mm dual bezel provides a nearly seamless digital canvas and extended operation. Modular construction let the company create any content using a system of displays. It is much brighter & more attractive solution compare to regular LCD and it will definitely catch the eye of the passersby.



FHD



Operation 24/7




Thin dual bezel




Landscape & portrait mode



Daisy chain connection



Modular



No gap



Low TCO

DIAGONAL SIZE, INCH / RATIO	54.64" (55") D-LED
RESOLUTION / R. FREQUENCY	1920 x 1080 Landscape & Portrait usage / 60Hz
BRIGHTNESS	500 cd/m2
COLOUR	1.07B (10 bit)
VIEWING ANGLE	H178°/V178°
RESPONSE TIME	8 ms
CONTRAST RATIO	1200:1
DYNAMIC CONTRAST	500 000 : 1
LIFETIME / OPERATING MODE	50 000 h min / 24/7
USB 2.0	1
DP OUT, DP IN, HDMI IN, USB 2.0	1/2/2/1
RS232 IN / RS232 OUT, LAN	1/1 RJ45, 1
UNIT DIMENSION (WXDXH), MM	1213.4x121.85x684.2 mm / Dual Bezel: 3.5 mm
PACKAGE DIMENSION (WXDXH), MM	1385x348x858 mm (2 pcs in one box)
WEIGHT (NET/GROSS), KG	28 kg / 31.5 kg (1 pcs in one box)
HOUSING MATERIAL/COLOR	Metal / Black
SURFACE TREATMENT	Hard coating (2H), Anti-glare low reflection treatment of the front polarizer (Haze 3% (Typ.))
OPERATING CONDITIONS	0°C to 40°C / 20% to 85%
POWER CONSUMPTION	200W / In standby: <0.5W
IN THE BOX	Power cable, user guide, Remote control, HDMI cable, IR receiver, Warranty card. VESA option on the LCD (600mm x 400mm), VESA kit is NOT included.
POWER SUPPLY	100V-240V, 50-60 Hz