

**PETROVÖLL MÖTPRO 4 STROKE MOTOR CYCLE OIL SAE 10W40**

PETROVÖLL MÖTPRO 4 STROKE CYCLE OIL SAE 10W40 is superior quality four-stroke motorcycle engine oil is primarily intended for general use in all types of four-stroke motorcycles and engines. It is formulated with highly refined Synthetic base stocks and state of art additive technology in order to provide good engine cleanliness, good wear protection and corrosion protection for all makes of Japanese, European and American Scooters, Bikes, ATV and dirt bike 4-stroke engines with integral or separate transmissions running on leaded or unleaded gasoline. It provides optimum protection for engines requiring multi grade oil.

**PERFORMANCE LEVEL**

- JASO T903:2011 AT MA-2 LEVEL ;, API SN

**PROPERTIES**

- Air & liquid-cooled 4T motorcycle engines
- Improved fuel economy and filterability.
- Enhanced thermal stability at high temperature.
- Suitable for motorcycles with exhaust catalytic converters.
- 4T gasoline engines fitted to portable power equipment, such as generators, mowers, etc
- Excellent protection against oxidation, foaming, low temperature sludge and high temperature deposits.
- Properly balanced detergent and dispersion ensures a clean engine.

**SPECIFICATION & TECHNICAL PARAMETER**

<b>Test</b>	<b>Result</b>
<i>Viscosity Grade</i>	<i>10W40</i>
<i>Kin. Viscosity @ 40 °C, cSt</i>	<i>99.52</i>
<i>Kin. Viscosity @ 100 °C, cSt</i>	<i>14.52</i>
<i>Viscosity Index</i>	<i>151</i>
<i>Density @ 15 °C, g/cm<sup>3</sup></i>	<i>0.8452</i>
<i>Foam Test, Sequence II, ml/ml</i>	<i>0/0</i>
<i>TBN, mg KOH/g</i>	<i>8.123</i>
<i>Flash Point COC, °C</i>	<i>236</i>
<i>Pour Point, °C</i>	<i>-36</i>