



# PRODUCT SPECIFICATION REPORT

All-Purpose High-Temperature is a multi-purpose grease fortified with special additives, enabling it to withstand the heavy impact and pounding pressures common to heavy equipment.

## ALL-PURPOSE HIGH-TEMPERATURE

PROD. #3121

Multi-Purpose, Anti-Spatter Grease



### FEATURES/BENEFITS:

Lubricates	Provides lubrication for a wide variety of parts and equipment
Stays Put	Lasts longer than many conventional greases, won't pound out
Extreme Pressure Additive	Excellent load carrying capability with a 65 lb. Timken OK load
Special Rust and Corrosion Inhibitors	Resists corrosion and the resulting seizing of fittings
Stable in Most Environments	Resists most acids, weather, dirt, water, steam, and oxidation

### APPLICATIONS:

All-Purpose High-Temperature provides superior protection to lubricate a wide variety of automotive, trucking, industrial, mining, and construction equipment. For use in: automotive repair shops, fabricated metal shops, motorcycle dealer, construction companies, industrial machinery manufacturers, new & used car dealers, electrical contractors, service stations, oil and natural gas drilling, various manufacturing applications, and other industrial processes.

### COMPANION PRODUCTS:

All-Purpose Lithium Grease, High-Performance Lithium Grease, Pipe Dope, Formula 50, Big Orange, Zep 45, Zep 40, Solv, ID Red, Zepride, Blue Marvel (EnviroEdge), T'N'T, Zep floor finishes, Zep brooms and mops, Zep gloves, Zep paper towels

### SPECIFICATIONS:

NLGI Grade (ASTM D-217)	2.5
Worked Penetration (ASTM D-217)	245-265
Thickener Type	Clay
Color	Green
Texture	Stringy, adhesive
Base Oil	Naphthenic Oil
Temperature Range	-0 to 400°F
Rust Prevention D-1743 Rating	PASS
Dropping Point D-556	>500°F
4-Ball Weld Load (ASTM D-2596)	400 kgf
Timken OK Load (ASTM D-2509)	65 lbs

### PACKAGING:

- 10 x 14 oz Cartridges 312104
- 40 x 14 oz Cartridges 312101
- 15 lb Pail 312115
- 45 lb Pail 312134
- 120 lb Drum 312142

Zep Sales & Service  
www.zep.com  
1-877 | BUY ZEP