

# Eaton 9E3000I

Catalog Number: 9E3000I

Eaton 9E UPS, 3000 VA, 2400W, Input: C20, Output: (6) C13, (1) C19, Tower



Photo is representative

## General specifications

Product Name	Catalog Number
Eaton 9E UPS	9E3000I
UPC	Product Length/Depth
786689166588	19 cm
Product Height	Product Width
33 cm	39.9 cm
Product Weight	Compliances
24.2 kg	CE Marked
	TUV

## Certifications

IEC/EN 62040-1  
IEC/EN 62040-2  
CE  
EAC

## Battery

### Battery type

Sealed, lead-acid

### Runtime graph

\$row.attributeValue.cdata

### Battery replacement

Replacable batteries

### Battery quantity

6

### Battery management

Automatic battery test

Deep discharge protection

### Battery rating

12 V / 9 Ah

### Extended battery capability

Yes

## Electrical output

### Receptacle

(6) C13, (1) C19

### Voltage

230V

### Wattage

2400 W

### Output power factor

0.8

### Output voltage range

220/230/240 V +/- 2%

### Output waveform

Sine wave

### Output nominal voltage

230V default (220/230/240V)

### Voltage distortion output (linear load) - max

3

### Feed type

1

### Topology

Online/Double-conversion

### VA rating

3000 VA

## Electrical input

### Input connection

C20

### Input nominal voltage

230V default (220/230/240V)

### Nominal frequency

50/60 Hz

### Input power factor

>.99

### Input voltage range

176-300 V (100 V-300 V with derating)

## Communications

### Includes network card

No

### Communication

USB port (HID compliant)

Serial port (RS232)

Communication slot

### Ethernet interface

No

### User interface

LCD Display

Input frequency range

40-70 Hz

Potential free switch contact

No

Expansion slots

One slot for optional communication card

Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power Protector

Type of interface

Other

## Environmental

Altitude

3000 m

Noise level

<37 dB at 1 meter

Temperature range

0° to 40°C (32° to 104°F)

Relative humidity

0-95% non-condensing

## Additional specifications

Construction type

Free standing model

Package contents

UPS

USB cable

Serial cable

Quickstart guide

Safety instructions

Phase (output)

1

Internal bypass

Yes

Auto shutdown function

Yes

Color

Black

Efficiency

91

Rack mounting kit

No

Phase (input)

1

Hot swap power

No

## Resources

[Declarations of conformity](#)

[EU Declaration of Conformity](#)

[Manuals and user guides](#)

[Eaton 9E 1kVA-3kVA UPS Eaton 9E EBM - Advance user guide](#)

[Technical data sheets](#)

[Eaton 9E UPS - Datasheet](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)