

# Eaton 9SX1000I

Catalog Number: 9SX1000I

Eaton 9SX UPS, 1000 VA, 900 W, Input: C14, Outputs: (6) C13, Tower

## General specifications



**Product Name**  
Eaton 9SX UPS

**UPC**  
743172090928

**Product Height**  
252 mm

**Product Weight**  
14.8 kg

**Catalog Number**  
9SX1000I

**Product Length/Depth**  
387 mm

**Product Width**  
160 mm

**Compliances**  
CE Marked  
TUV  
cULus Listed  
CSA 22.2  
FCC part 15 Class B  
CISPR22 Class B

**Certifications**  
IEC/EN 62040-1  
UL 1778  
IEC/EN 62040-2  
CE  
cULus Listed  
EAC

## Battery

### Battery type

Sealed, lead-acid

### Runtime graph

\$row.attributeValue.cdata

### Battery replacement

Hot-swappable internal batteries and extended battery modules (EBMs)

### Battery quantity

3

### Battery management

ABM & Temperature compensated charging method (user selectable)  
Automatic battery test  
Deep discharge protection  
Automatic recognition of external battery units

### Battery rating

12 V / 9 Ah

### Extended battery capability

Yes

## Electrical output

### Receptacle

(6) C13

### Voltage

230V

### Wattage

900 W

### Output power factor

0.9

### Output voltage range

200/208/220/230/240 V +/- 2%

### Output waveform

Sine wave

### Output nominal voltage

230V default (200/208/220/230/240V)

### Voltage distortion output (linear load) - max

3

### Feed type

1

### Topology

Online/Double-conversion

### VA rating

1000 VA

## Electrical input

### Input connection

C14

### Input nominal voltage

230V default (200/208/220/230/240/250V)

### Nominal frequency

50/60 Hz

### Input power factor

>.99

### Input voltage range

190-276 Vac without derating (up to 120-276 Vac with derating)

## Communications

### Includes network card

No

### Communication

USB port (HID compliant)

Serial port (RS232)

Mini-terminal block for remote power off

Mini-terminal block for output relay

Dry contacts (2 outputs, 1 input, optocoupler, DB9)

Input frequency range

40-70 Hz

Ethernet interface

No

User interface

Multilingual graphical LCD display

Potential free switch contact

Yes

Expansion slots

One slot for optional communication card

Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power Protector

Type of interface

Other

## Environmental

Altitude

3000 m

Noise level

<41 dB at 1 meter

Temperature range

0° to 40°C (32° to 104°F)

Relative humidity

0-96% non-condensing

## Additional specifications

Construction type

Free standing model

Package contents

UPS  
(2) IEC-IEC output cables  
USB cable  
Serial cable  
Safety instructions  
Quickstart guide

Phase (output)

1

Internal bypass

Yes

Auto shutdown function

Yes

Color

Black

Efficiency

89

Rack mounting kit

No

Phase (input)

1

Hot swap power

No

## Resources

### Brochures

[Eaton UPS and battery services - EN](#)

[Eaton UPS Services Quick Guide - EN](#)

### Compliance information

[EU declaration of conformity Eaton 9SX UPS](#)

### Manuals and user guides

[Eaton 9SX UPS - 0-6KVA - Installation and user manual](#)

### Technical data sheets

[Eaton 9SX UPS 700/1000/1500/2000/3000 VA - Datasheet](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)