

# Product datasheet

Specifications



Easy UPS 1 Ph On-Line, 3kVA,  
Rackmount 4U, 230V, 6x IEC C13 +  
1x IEC C19 outlets, Intelligent Card  
Slot, LCD, Extended Runtime, W/  
rail kit

SRVS3KRILRK

## Overview

**Presentation** High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.

**Lead time** Usually in Stock

## Main

**Main Input Voltage** 230 V

**Product or component type** Uninterruptible power supply (UPS)

**Other Input Voltage** 220 V  
240 V

**Main Output Voltage** 230 V

**Other Output Voltage** 220 V  
240 V

**Rated power in W** 2400 W

**Rated power in VA** 3000 VA

**Input Connection Type** IEC 60320 C20

**output connection type** 6 IEC 60320 C13  
1 IEC 60320 C19

**Number of rack unit** 4U

**Number of cables** 1

**Provided equipment** 1 IEC 60320 C19 to Schuko power cable  
1 IEC 60320 C13 to C14 power cable  
1 USB cable  
1 RS-232 configuration cable  
2 rack mounting brackets  
2 rack mounting support rails  
1 external battery pack  
1 battery cable

**Range of product** Easy UPS 1Ph On-Line

## Batteries & Runtime

**Run Time** [View Runtime Graph](#)

**Efficiency** [View Efficiency Graph](#)

**Battery type** Lead-acid battery

**Battery voltage** 72 V

**Extended runtime** 1

**Number of battery filled slots** 0

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Number of battery free slots	0
Battery recharge time	4 h
Battery life	3...5 year(s)
Battery charger power	350 W rated

## General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

## Physical

Colour	Black (RAL 7010)
Height	17.2 cm
Width	43.7 cm
Depth	63.2 cm
Net weight	52 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
USB compatible	Yes
Mounting position	Horizontal

## Input

Input voltage limits	110...285 V half load 160...280 V full load
Input protection type	Circuit breaker and fuse
Network frequency	40...70 Hz auto sensing

## Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	88 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

## Conformance

Product certifications	CE UKCA
------------------------	------------

<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
------------------	--

## Environmental

<b>Ambient air temperature for operation</b>	0...40 °C
<b>Relative humidity</b>	0...95 % non-condensing
<b>Operating altitude</b>	0...3000 m
<b>Ambient air temperature for storage</b>	-20...50 °C
<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Storage altitude</b>	0...15000 m
<b>Acoustic level</b>	50 dBA
<b>Heat dissipation</b>	910 Btu/h
<b>IP degree of protection</b>	IP20

## Communications & Management

<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
<b>control panel</b>	Multifunction LCD status and control console

## Surge Protection and Filtering

<b>Surge energy rate</b>	600 J
--------------------------	-------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	3
<b>Package 1 Height</b>	48 cm
<b>Package 1 Width</b>	60 cm
<b>Package 1 Length</b>	80 cm
<b>Package 1 Weight</b>	66.8 kg

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

[EU RoHS Directive](#)

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

## Use Again

### Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)

Removable battery

User replaceable

WEEE

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Take-back

No