

# Specifications

## Eaton 9SX6KIRT3UG2



Eaton 9SX Gen2 UPS, 6000 VA, 6000 W,  
Input: Hardwired, Outputs: (8) C13, (3) C19,  
Hardwired, Rack/tower, 3U, Rack-mounting  
kit included

Photo is representative



### General specifications

<b>PRODUCT NAME</b>	Eaton 9SX Gen2 UPS
<b>CATALOG NUMBER</b>	9SX6KIRT3UG2
<b>MODEL CODE</b>	Eaton 9SX 6000i RT3U G2
<b>EAN</b>	3553340710667
<b>PRODUCT LENGTH/DEPTH</b>	684 mm
<b>PRODUCT HEIGHT</b>	130 mm
<b>PRODUCT WIDTH</b>	440 mm
<b>PRODUCT WEIGHT</b>	43.1 kg
<b>WARRANTY</b>	2 year

<b>COMPLIANCES</b>	LVD Directive (CB) EMC Directive RoHS Directive REACH WEEE Directive Packaging Directive Batteries Directive
<b>CERTIFICATIONS</b>	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 ENERGY STAR certified CE cULus UKCA Cm Ukr RCM KCC BSMI



Powering Business Worldwide

## Additional specifications

**CONSTRUCTION TYPE** 482.6 mm (19 inch) device

**PACKAGE CONTENTS**

- UPS
- (2) cable glands
- (2) IEC-IEC output cables (1,2m)
- USB cable (1,8m)
- Cable locking systems
- Supports for tower mounting
- Rack-mounting kit with brackets and slides for UPS
- Safety instructions
- Quickstart guide

**INTERNAL BYPASS** Yes

**AUTO SHUTDOWN FUNCTION** Yes

**COLOR** Black

**EFFICIENCY AT MAX. LOAD** 96.5

**RACK MOUNTING KIT** Yes

**HOT SWAP POWER** No

## Battery

**BATTERY TYPE** Sealed, lead-acid

**RUNTIME GRAPH** [View runtime graph](#)

**BATTERY REPLACEMENT** Hot-swappable internal batteries and extended battery modules (EBMs)

**BATTERY QUANTITY** 15

**BATTERY MANAGEMENT**

- ABM+ (Predictive battery life) & Temperature compensated charging method (user selectable)
- Automatic battery test
- Deep discharge protection
- Automatic recognition of external battery units

**BATTERY RATING** 12 V / 5 Ah

**EXTENDED BATTERY CAPABILITY** Yes

## Communications

**INCLUDES NETWORK CARD** No

### COMMUNICATION

- USB port (HID compliant)
- Serial port (RS232)
- Mini terminal block for remote On/Off
- Mini-terminal block for remote power off
- Mini-terminal block for dry contacts outputs (2 contacts)

**ETHERNET INTERFACE** No

**USER INTERFACE** Multilingual graphical LCD display

**POTENTIAL FREE SWITCH CONTACT** Yes

**EXPANSION SLOTS** One slot

**SOFTWARE COMPATIBILITY** Eaton Brlightlayer Software suite

**TYPE OF INTERFACE** Other

## Electrical output

**RECEPTACLE** (8) C13, (3) C19, Hardwired

**VOLTAGE** 230V

**VA RATING** 6000 VA

**WATTAGE** 6000W

**OUTPUT POWER FACTOR** 1

**OUTPUT WAVEFORM** Sine wave

**OUTPUT NOMINAL VOLTAGE** 230V default (200/208/220/230/240V)

**VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX** 1

**FEED TYPE** 1

**TOPOLOGY** Online/Double-conversion

## Electrical input

**NOMINAL FREQUENCY** 50/60 Hz

**INPUT POWER FACTOR** >.99

**INPUT VOLTAGE RANGE** 176-276 V (100-276 V with derating)

**INPUT FREQUENCY RANGE** 40-70 Hz

## Environmental

**ALTITUDE** 3000 m

**NOISE LEVEL** <40 dB at 1 meter

**TEMPERATURE RANGE** 0° to 40°C (32° to 104°F)

**RELATIVE HUMIDITY** 0-95% non-condensing

## Resources

BROCHURES	<a href="#">Eaton 9SX Gen2 UPS Datasheet - EN</a>
COMPLIANCE INFORMATION	<a href="#">Eaton single phase UPS Transportation document according to DGR</a>
DECLARATIONS OF CONFORMITY	<a href="#">Eaton 9SX Gen2 Declaration of Conformity</a>
MANUALS AND USER GUIDES	<a href="#">Eaton 9SX Gen2 UPS Advanced User Guide - EN</a>
PEP ECO-PASSPORT	<a href="#">eaton-double-conversion-network-ups-pep-eato-00282-v0102-en.pdf</a> <a href="#">eaton-double-conversion-network-ups-pep-eato-00281-v0102-en.pdf</a>

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

