

wellex
PROFESSIONAL FM TRANSCEIVER



Support
TYPE-C charger



PROFESSIONAL FM TRANSCEIVER

F-5

Ultra Output Power Design
Ultra Long Time Standby
16 Memory Channels
Sid Key Assignment

wellex
PROFESSIONAL FM TRANSCEIVER

Support
TYPE-C charger

F-5



PROFESSIONAL FM TRANSCEIVER
Ultra Output Power Design
Ultra Long Time Standby
16 Memory Channels
Sid Key Assignment

SPECIFICATION

GENERAL		TRANSMIT PART	
Frequency Range	VHF: 136~174MHz UHF: 400~480MHz	RF Power	5W
Operating Temperature	-20°C~+60°C	Modulate Mode (W/N)	16KΦF3E,11KΦF3E
Frequency Combination	Phase lock frequency synthesize	Max. Freq. Deviation (W/N)	<5K / <2.5KHz
Frequency Stability	±2.5ppm	Remain Wave Radiation	<-60dB
Memory Channel	16 Channels	Transmitting Current	≤1300mA
Working voltage	DC 7.4V	RECEIVE PART	
Antenna Impedance	50Ω	Sensitivity	<0.25μV(12dB SINAD)
Operating Mode	Simplex of co-frequency or alien frequency	Squelch Sensitivity	<0.20μV
Dimension	125mm×65mm×35mm	Intermodulation Antijamming	50dB
Weight	150g (Include Battery Pack)	Audio Power output	500mW
		Receiving Current	≤100mA
		Squelch Standby	20mA

Notice: Saving your presence, no additional notice will be sent if specification changes because of technology-improving.