



FEATURES

1. Application Field: Pneumatic, Oil pressure and Hydraulic systems.
2. Function: to reduce noise and to remove dust and water.
3. Pressure Range: 0-10 bar; Max. Pressure: 12 bar.
4. Temperature Range: -10~70 °C.
5. Noise Elimination Effect: 20-25 db.
6. Filtration Rating: 5-100µm; regular rating is 40µm.
7. NPT, G & BSPT thread are available; regular thread is G thread.
8. Material: Brass, SS304, SS316, HDPE, NYLON.



HOW TO ORDER

Thread Code:

06 = 1/8"; 08 = 1/4";

10 = 3/8"; 15 = 1/2";

20 = 3/4"; 25 = 1";

32 = 1 1/4"; 40 = 1 1/2";

50 = 2"; 60 = 3";

70 = 6".

SS316 SILENCER



BS

Model [T]

Barb (mm)-Filter length (mm)

BS-6-25MM 6MM-25MM

BS-6-50MM 6MM-50MM

CONE SILENCER



A

Model [T]

Thread(G, PT, NPT)

A-M5 M5

A-6 1/8"

A-8 1/4"

A-10 3/8"

A-15 1/2"

A-20 3/4"

A-25 1"

A-32 1 1/4"

A-40 1 1/2"

A-50 2"

FLAT SILENCER



V

Model [T]

Thread(G, PT, NPT)

V-M5 M5

V-6 1/8"

V-8 1/4"

V-10 3/8"

V-15 1/2"

V-20 3/4"

V-25 1"

V-32 1 1/4"

V-40 1 1/2"

V-50 2"

EXHAUST THROTTLE



B

Model [T]

Thread(G, PT, NPT)

B-6	1/8"
B-8	1/4"
B-10	3/8"
B-15	1/2"
B-20	3/4"
B-25	1"

EX-PROOF THROTTLE



C

Model [T]

Thread(G, PT, NPT)

C-6	1/8"
C-8	1/4"
C-10	3/8"
C-15	1/2"
C-20	3/4"
C-25	1"

TIMING MUFFLER



SD

Model [T]

Thread(G, PT, NPT)

SD-6	1/8"
SD-8	1/4"
SD-10	3/8"
SD-15	1/2"
SD-20	3/4"
SD-25	1"

SLOT SILENCER



PDK

Model [T]

Thread(G, PT, NPT)

PDK-6	1/8"
PDK-8	1/4"
PDK-10	3/8"
PDK-15	1/2"
PDK-20	3/4"
PDK-25	1"

CONE SILENCER



AN

Model [T]

Thread(G, PT, NPT)

AN-6	1/8"
AN-8	1/4"
AN-10	3/8"
AN-15	1/2"
AN-20	3/4"
AN-25	1"

FLAT SILENCER



VN

Model [T]

Thread(G, PT, NPT)

VN-6	1/8"
VN-8	1/4"
VN-10	3/8"
VN-15	1/2"
VN-20	3/4"
VN-25	1"

SLOT SILENCER



VB

Model [T]

Thread(G, PT, NPT)

VB-6	1/8"
VB-8	1/4"
VB-10	3/8"
VB-15	1/2"
VB-20	3/4"
VB-25	1"

SLOT SILENCER



D

Model [T]

Thread(G, PT, NPT)

D-6	1/8"
D-8	1/4"
D-10	3/8"
D-15	1/2"
D-20	3/4"
D-25	1"

CONE SILENCER



E

Model [T]

Thread(G, PT, NPT)

E-6	1/8"
E-8	1/4"
E-10	3/8"
E-15	1/2"
E-20	3/4"
E-25	1"

CONE SILENCER



F

Model [T]

Thread(G, PT, NPT)

F-6	1/8"
F-8	1/4"
F-10	3/8"
F-15	1/2"
F-20	3/4"
F-25	1"

CONE SILENCER



SSM

Model [T]

Thread(G, PT, NPT)

SSM-6	1/8"
SSM-8	1/4"
SSM-10	3/8"
SSM-15	1/2"
SSM-20	3/4"
SSM-25	1"

FLAT SILENCER



SSV

Model [T]

Thread(G, PT, NPT)

SSV-6	1/8"
SSV-8	1/4"
SSV-10	3/8"
SSV-15	1/2"
SSV-20	3/4"
SSV-25	1"

MESH MUFFLER



SSDV

Model [T]

Thread(G, PT, NPT)

SSDV-6	1/8"
SSDV-8	1/4"
SSDV-10	3/8"
SSDV-15	1/2"
SSDV-20	3/4"
SSDV-25	1"

MESH MUFFLER



SDV

Model [T]

Thread(G, PT, NPT)

SDV-6	1/8"
SDV-8	1/4"
SDV-10	3/8"
SDV-15	1/2"
SDV-20	3/4"
SDV-25	1"

MESH SILENCER



DV

Model [T]

Thread(G, PT, NPT)

DV-6	1/8"
DV-8	1/4"
DV-10	3/8"
DV-15	1/2"
DV-20	3/4"
DV-25	1"

STEEL MUFFLER



ST

Model [T]

Thread(G, PT, NPT)

ST-6	1/8"
ST-8	1/4"
ST-10	3/8"
ST-15	1/2"
ST-20	3/4"
ST-25	1"
ST-40	1 1/2"
ST-50	2"

PLASTIC MUFFLER



SU

Model [T]

Thread(G, PT, NPT)

SU-6	1/8"
SU-8	1/4"
SU-10	3/8"
SU-15	1/2"
SU-20	3/4"
SU-25	1"

PLASTIC MUFFLER



PSU

Model [T]

Thread(G, PT, NPT)

PSU-M5	M5
PSU-6	1/8"
PSU-8	1/4"
PSU-10	3/8"
PSU-15	1/2"
PSU-20	3/4"
PSU-25	1"

PLASTIC MUFFLER



PSE

Model [T]

Thread(G, PT, NPT)

PSE-M5	M5
PSE-6	1/8"
PSE-8	1/4"
PSE-10	3/8"
PSE-15	1/2"
PSE-20	3/4"
PSE-25	1"

COMPRESSOR MUFFLER



XY

Model [T]

Thread(G, PT, NPT)

XY-15	1/2"
XY-20	3/4"
XY-25	1"
XY-32	1 1/4"
XY-40	1 1/2"
XY-50	2"
XY-60	3"
XY-70	6"