

CL1000 (CL1000M: 17" LCD)

Slideaway™ LCD Console

• The CL1000 is a LCD KVM console that serves as the front-end for standard KVM switches. The CL1000 features an integrated 17" LCD panel, full keyboard, and touchpad in a 1U, rack-mountable, Slideaway™ housing. Users who already have a switch can take advantage of the space saving and efficiency benefits of the CL1000 LCD KVM console without the unnecessary expense of having to purchase a KVM switch.










Features

- Integrated KVM console with 17" LCD monitor in a Slideaway™ housing
- LCD module rotates up to 115 degrees for a more comfortable viewing angle
- Slideaway™ housing is less than 1U with top and bottom clearance for smooth operation in a 1U high system rack
- Compatible with most PS/2 KVM Switches
- Internal power built in
- Adjustable depth to fit within a rack
- High video resolution:Up to 1280 x 1024 @75Hz Supports DDC, DDC2, DDC2B
- DDC emulation VGA settings of every connected computer are automatically adjusted for optimal output to the LCD monitor
- Keyboard Language support: English(US); English(UK); German; German(Swiss); French; Spanish; Traditional Chinese; Japanese; Korean; Swedish; Italian; Russian; Hungarian
- Improved design single person installation (optional)

Rack Mount Kit	Depth (cm)
Long(Optional)	68 - 100
Short (Standard)	42 - 72

Easy Installation Rack Mount Kit	Depth (cm)
Long(Optional)	68 - 105
Short(Optional)	42 - 70



PS/2 KVM Switch

Specification

Fi	unction	CL1000	
Connectors	KVM Ports	Keyboard / Video / Mouse	1 x SPHD Female (Yellow)
	Power		1 x 3-prong AC Socket
Switches	LCD Adjustment		4 x Pushbutton
	Reset		1 x Semi-recessed Pushbutton
	Power		1 x Rocker
LEDs	Power		1 (Dark Green)
	Num Lock		1 (Green)
	Caps Lock		1 (Green)
	Scroll Lock		1 (Green)
Emulation	1117-1111111111111111111111111111111111		PS/2
Video			1280 x 1024; DDC2B
I/P Rating			100 - 240 VAC; 50/60 Hz; 1A
Power Consumption	ower Consumption 17" LCD		120V, 27W / 230V, 35W
Environment	Operating Temp.		0-40°C
	Storage Temp.		-20-60°C
	Humidity		0-80% RH, Non-condensing
	Housing		Metal+Plastic
nysical Properties	Weight	17" LCD	12.30 kg
	Dimensions (D x W x H)		53.83 x 48.00 x 4.40 cm

^{*} The specifications and pictures are subject to change without notice.

ATEN International Co., Ltd.

Printed 07/2014 V5.0



