

Mic-drain 标准型 Standard model

	 	
产品型号 Product model	MIC-A	MIC-B
产品特点 Product features	分体式 (L 型) Split type (L-type)	一体式 (直线型) Integrated type (line-type)
定时时间调节范围 Timer cycle range (ON/OFF)	ON: 0.5 - 10 Sec. OFF: 0.5 - 45 Min.	
工作压力 Rated working pressure	0~1.6 Mpa	
0.8Mpa 时电磁阀排水能力 Discharge capacity at 0.8Mpa	大约 160 ml/s About 160 ml/s	
适用介质 Applicable media	水、含油冷凝水 Water, Oil-containing condensate	
介质温度 Temperature of medium	1~60℃	
环境温度 Temperature of ambient	1~60℃ (零下温度可选用加热型) 1~60℃ (Heating model is optional for sub-zero temperature)	
过滤器入口/出口尺寸 Inlet/Outlet of ball valve strainer	入口: 外螺纹 R1/2", 内螺纹 Rc1/4" 可选 出口: 外螺纹 R1/2", R1/4" 可选 Inlet: Male R1/2", Female Rc1/4" Outlet: Male R1/2", Rc1/4" Optional	/
电磁阀入口/出口尺寸 Inlet/Outlet of solenoid valve	入口: 内螺纹 Rc1/2"、Rc1/4" 可选 出口: 内螺纹 Rc1/2"、Rc1/4" 可选 Inlet: Female Rc1/2", Rc1/4" Optional Outlet: Female Rc1/2", Rc1/4" Optional	入口: 外螺纹 R1/2" 出口: 内螺纹 Rc1/2" Inlet: Male R1/2" Outlet: Female Rc1/2"
排放阀类型 Type of discharge valve	直动型电磁阀 Direct acting solenoid valve	
排水流量孔径 Valve orifice	3.2 mm	
排放阀前置过滤网 Front mesh strainer of discharge valve	有 (外置) Yes (Outer set)	
阀体材质 Material of valve body	黄铜 Brass	
手动排水功能 Manual function	有 Yes	
防护等级 Protection class	IP65 (正确装配后) IP65 (After correct assembly)	