Oct 22, 2026

Product data sheet

HF422

Characteristics

Auxiliary contacts, HDC3, F4-22, top, 2 NO + 2 NC



Main

Range of product	HDC3
Product or component type	Auxiliary contact block
Mounting location	Top
Auxiliary contact composition	2 NC

Complementary

Product compatibility	HDC3 contactor 6…95 A HDC3 contactor 120…630 A
Auxiliary contacts operation	Instantaneous
Shielding continuity terminal	Without
[Ui] rated insulation voltage	380 V conforming to IEC 60947-5-1
[Ith] conventional free air thermal current	10 A

Environment

Environmental characteristic	Harsh environment
Standards	IEC 60947-5-1
Product certifications	SEMKO
IP degree of protection	IP20
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-25…70 °C
Operating altitude	2000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable packaging	No

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.