

Metalworking Products ...the all-inclusive high performance range.

MCC High Performance Metalworking Compound

- A low melt point metalworking compound for use with all metals, including the more difficult metals and alloys such as titanium and nimonics.
- Based on EP additives fortified with MoS₂ to provide excellent extreme pressure performance and lubricity.
- Improves cutting performance, providing a better surface finish.

Available in 450g or 3kg tins.



MWF High Performance Metalworking Fluid

- A molybdenised organic oil, reinforced with EP compounds, to give high film strength, anti-weld and extreme pressure properties.
- Can be used neat for extreme applications to reduce heat and improve dimensional stability and surface finish or may be added to reinforce straight cutting oils already in use.
- Particularly effective on stainless steel and light alloys, which are prone to surface welding or pick-up on the tool.

Available in 350ml squeeze bottle, 5 litre, 25 litre or 205 litre containers.



MWS High Performance Metalworking Spray

- Aerosol spray version of MWF for easy application.

Available in 400ml aerosol.



MOLYSLIP®

MSO Soluble Cutting Oil

- For dilution at 1 part to between 10 and 30 parts of water, for use in all operations which require a general purpose cutting oil.
- Practically odourless. For use in all manual and re-circulating cutting systems.
- MSO Clear is available for operations requiring visibility - thread cutting etc.

Available in 5 litre, 25 litre or 205 litre containers.

MEP Extreme Pressure Additive

- Additive for soluble cutting oils to improve lubricating and antiweld properties.
- Contains high proportions of emulsifying agents and anti-weld additives and a stable, soluble molybdenum compound.
- Also used as a super EP Soluble Oil in its own right.

Available in 5 litre, 25 litre or 205 litre containers.

MTG Metalworking Machine Tool Grease

- For all lubrication points on machine tools.
- High melt point, and resistant to water and soluble oil dilutions
- Contains EP additives and MoS₂ to prolong lubrication intervals.

Available in 450g or 5kg tins.



For further information on these or other products in the MolySlip range, please contact your dealer or:

MOLYSLIP ATLANTIC LIMITED
A1 Danebrook Court, Langford Lane, Kidlington
Oxfordshire OX5 1LQ
Tel: +44 (0)1865 370032 Fax: +44 (0)1865 372030
Email: enquiries@moly Slip.co.uk
Website: www.moly Slip.co.uk