

Main

Range	EasyPact
Device short name	LAET
Product or component type	Time delay auxiliary
Product compatibility	EasyPact TVS contactor
Auxiliary contacts operation	On-delay contact
Pole contact composition	1 NO + 1 NC
Connections - terminals	Control circuit : screw clamp terminals 2 cable 2.5 mm ² - external diameter: 6 mm - cable stiffness: solid or flexible - without cable end cable end Control circuit : screw clamp terminals 2 cable 2.5 mm ² - external diameter: 6 mm - cable stiffness: solid or flexible - with cable end cable end Control circuit : screw clamp terminals 1 cable 1 mm ² - external diameter: 6 mm - cable stiffness: solid or flexible - without cable end cable end Control circuit : screw clamp terminals 1 cable 1 mm ² - external diameter: 6 mm - cable stiffness: solid or flexible - with cable end cable end

Complementary

Mounting location	Front
[Ui] rated insulation voltage	690 V - for control circuit - conforming to IEC 60947-5-1
[Ue] rated operational voltage	<= 690 V
[Ith] conventional free air thermal current	8 A at <= 60 °C
Irms rated making capacity	140 A AC conforming to IEC 60947-5-1
[Icw] rated short-time withstand current	140 A 100 ms 120 A 500 ms 100 A 1 s
Protection type	GG fuse 10 A
Mechanical durability	10 Mcycles
Minimum switching current	5 mA
Minimum switching voltage	17 V
Non-overlap time	1.5 ms on de-energisation (no overlap between NC and NO contact) 1.5 ms on energisation (no overlap between NC and NO contact)
Time delay range	1...30 s
Insulation resistance	> 10 MOhm
Product weight	0.06 kg

Environment

Environmental characteristic	Standard environment
Standards	IEC 60947-5-1
Product certifications	GOST
IP degree of protection	IP20 conforming to IEC 60529
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating derating in temperature

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Not Green Premium product
REACH	Reference not containing SVHC above the threshold
