

Main

Range of product	TeSys E
Product or component type	Thermal overload relay
Device short name	LRE
Relay application	Overload protection
Product compatibility	LC1E06...38
Network type	AC

Complementary

Network frequency	50...60 Hz
[Ue] rated operational voltage	<= 690 V AC
[Ui] rated insulation voltage	690 V AC power circuit IEC 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV
Mounting support	110 mm centre independent mounting 50 mm centre independent mounting Rail
Overload tripping class	Class 10A IEC 60947-4-1
Signalling function	Relay trip indicator
Thermal protection adjustment range	1.6...2.5 A
Tripping threshold	1.14 +/- 0.06 I _r IEC 60947-4-1
Connections - terminals	Screw clamp terminal power circuit 1 1...6 mm ² solid without Screw clamp terminal power circuit 1 1...4 mm ² flexible with Screw clamp terminal power circuit 1 1.5...6 mm ² flexible without Screw clamp terminal control circuit 1 2...5 mm ² solid without Screw clamp terminal control circuit 1 2...5 mm ² flexible with Screw clamp terminal control circuit 1 2...5 mm ² flexible without
Tightening torque	1.7 N.m power circuit screw clamp terminal 1...6 mm ² 1.7 N.m power circuit screw clamp terminal 1...4 mm ² 1.7 N.m power circuit screw clamp terminal 1.5...6 mm ² 1.7 N.m control circuit screw clamp terminal 2...5 mm ²
[I _{th}] conventional free air thermal current	5 A control circuit
Surge withstand	6 kV IEC 60801-5
Permissible current	1.6...2.5 A power circuit
Protection type	GG fuse 6 A power circuit AM fuse 4 A power circuit
Phase failure sensitivity	Tripping current 130 % of I _r on two phase, the last one at 0 IEC 60947-4-1
Reset	Manual or automatic reset compensated relay
Temperature compensation	-20...60 °C
Height	86 mm
Width	45 mm
Depth	70 mm
Product weight	0.13 kg

Environment

Standards	IEC 60947-4-1 IEC 60947-5-1
Product certifications	GOST
IP degree of protection	IP20 IEC 60529
Protective treatment	TH IEC 60068
Ambient air temperature for operation	-20...70 °C with derating -20...60 °C without derating IEC 60947-4-1
Ambient air temperature for storage	-60...80 °C
Operating position	Any position without in relation to normal vertical mounting plane
Fire resistance	850 °C IEC 60068-2-1
Shock resistance	6 gn 11 ms IEC 60068-2-7
Vibration resistance	3 gn IEC 60068-2-6
Dielectric strength	6000 V 50 Hz IEC 60255-5

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 1110 - Schneider Electric declaration of conformity

Contractual warranty

Period	18 months
--------	-----------