

### Main

Range of product	TeSys E
Product or component type	Thermal overload relay
Device short name	LRE
Product compatibility	LC1E120...300
Network type	AC

### Complementary

Network frequency	50...60 Hz
[Ue] rated operational voltage	<= 690 V AC
[Ui] rated insulation voltage	690 V AC power circuit IEC 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV
Mounting support	Mounting plate independent mounting
Overload tripping class	Class 10A IEC 60947-4-1
Thermal protection adjustment range	58...81 A
Tripping threshold	1.14 +/- 0.06 I <sub>r</sub> IEC 60947-4-1
Connections - terminals	Screw clamp terminal control circuit 1 2...5 mm <sup>2</sup> solid without Screw clamp terminal control circuit 1 2...5 mm <sup>2</sup> flexible with Screw clamp terminal control circuit 1 2...5 mm <sup>2</sup> flexible without Bars power circuit 6 25 mm Pitch power circuit 50 mm
Tightening torque	1.7 N.m control circuit screw clamp terminal 2...5 mm <sup>2</sup> 35 N.m power circuit lugs M10 35 N.m power circuit bar M10
[I <sub>th</sub> ] conventional free air thermal current	5 A control circuit
Surge withstand	6 kV IEC 60801-5
Permissible current	58...81 A power circuit
Protection type	GG fuse 125 A power circuit AM fuse 100 A power circuit
Phase failure sensitivity	Tripping current 130 % of I <sub>r</sub> on two phase, the last one at 0 IEC 60947-4-1
Reset	Manual or automatic reset compensated relay
Temperature compensation	-20...60 °C
Height	130 mm
Width	192 mm
Depth	117 mm
Product weight	1.67 kg

### Environment

Standards	IEC 60947-4-1 IEC 60947-5-1
Product certifications	GOST
IP degree of protection	IP00 IEC 60529
Protective treatment	TH IEC 60068
Ambient air temperature for operation	-20...70 °C with derating -20...60 °C without derating IEC 60947-4-1

Ambient air temperature for storage	-60...80 °C
Operating position	Any position without in relation to normal vertical mounting plane
Fire resistance	850 °C IEC 60068-2-1
Shock resistance	6 gn 11 ms IEC 60068-2-7
Vibration resistance	3 gn IEC 60068-2-6
Dielectric strength	6000 V 50 Hz IEC 60255-5

### Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

### Contractual warranty

Period	18 months
--------	-----------