

Main

| | |
|---------------------------|------------------------|
| Range of product | TeSys E |
| Product or component type | Thermal overload relay |
| Device short name | LRE |
| Product compatibility | LC1E120...300 |
| Network type | AC |

Complementary

| | |
|--|--|
| Network frequency | 50...60 Hz |
| [Ue] rated operational voltage | <= 690 V AC |
| [Ui] rated insulation voltage | 690 V AC power circuit IEC 60947-4-1 |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Mounting support | Mounting plate independent mounting |
| Overload tripping class | Class 10A IEC 60947-4-1 |
| Thermal protection adjustment range | 84...135 A |
| Tripping threshold | 1.14 +/- 0.06 I _r IEC 60947-4-1 |
| Connections - terminals | Screw clamp terminal control circuit 1 2...5 mm ² solid without Screw clamp terminal control circuit 1 2...5 mm ² flexible with Screw clamp terminal control circuit 1 2...5 mm ² flexible without Bars power circuit 6 25 mm Pitch power circuit 50 mm |
| Tightening torque | 1.7 N.m control circuit screw clamp terminal 2...5 mm ² 35 N.m power circuit lugs M10 35 N.m power circuit bar M10 |
| [I _{th}] conventional free air thermal current | 5 A control circuit |
| Surge withstand | 6 kV IEC 60801-5 |
| Permissible current | 84...135 A power circuit |
| Protection type | GG fuse 200 A power circuit AM fuse 160 A power circuit |
| Phase failure sensitivity | Tripping current 130 % of I _r on two phase, the last one at 0 IEC 60947-4-1 |
| Reset | Manual or automatic reset compensated relay |
| Temperature compensation | -20...60 °C |
| Height | 130 mm |
| Width | 192 mm |
| Depth | 117 mm |
| Product weight | 1.67 kg |

Environment

| | |
|---------------------------------------|---|
| Standards | IEC 60947-4-1 IEC 60947-5-1 |
| Product certifications | GOST |
| IP degree of protection | IP00 IEC 60529 |
| Protective treatment | TH IEC 60068 |
| Ambient air temperature for operation | -20...70 °C with derating -20...60 °C without derating IEC 60947-4-1 |

| | |
|-------------------------------------|--|
| Ambient air temperature for storage | -60...80 °C |
| Operating position | Any position without in relation to normal vertical mounting plane |
| Fire resistance | 850 °C IEC 60068-2-1 |
| Shock resistance | 6 gn 11 ms IEC 60068-2-7 |
| Vibration resistance | 3 gn IEC 60068-2-6 |
| Dielectric strength | 6000 V 50 Hz IEC 60255-5 |

Offer Sustainability

| | |
|--------------------------|---------------------------|
| Sustainable offer status | Not Green Premium product |
|--------------------------|---------------------------|

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|