

BC Petro Tape Series

Perfect Anti-Corrosion and great cost-saving Tape for any metals and pipe lines.

Features

- Provides excellent corrosion protection on steel structures (pipes, valves, flanges, couplings, pilings, etc) and creates a solid water barrier
- Composed of synthetic fabric with petrolatum compound, fillers and special anti-corrosion agents
- Good resistance to acids, alkalis and salts

Characteristics

- Conforms to irregular surfaces
- Great efficiency with easy application and short working times
- No changes in quality under extremely low temperature(-270 °C)
- No cracking, No hardening & solvent free
- Can be applied on the cold & wet surfaces
- Encapsulates lead paints

Uses

- Hydraulic pipes, valves, flanges, elbows and tees
- Underground pipes or tanks
- Steel pilings or marine structures







Corrosion protection for Steel Pipes





BC PETRO TAPE SERIES

- Heat-resistant Tape (H Type)
 Provides excellent temperature suitability
 (Service Temperature: -270°C ~ 80°C)
- Soft and Standard Tape (S Type)
 Soft and wet and outstanding corrosion protection ability

(Service Temperature: -270°C ~ 60°C)

■ BC PETRO PASTE

Primer for increasing adhesion and anti- corrosive property of BC Petro Tape

- Standard type
 Can be applied on wide range of working places
- Under Water type
 Designed for under-water application
- BC PETRO MASTIC
 Filler or sealer on the uneven surfaces
- OUTER WRAPPING TAPE (Option) PVC Firm Tape is recommended







BC Petro Paste



BC Petro Mastic



PVC Firm Tape



Sizes/Packings

BC PETRO TAPE

IMPA Code	Sizes (W×T×L)	Packings	ISSA Code
81 24 71	50mm × 1.2mm × 10m	36rls/box	75 550 01
72	100mm × 1.2mm × 10m	18rls/box	02
73	150mm×1.2mm×10m	12rls/box	03
74	200mm × 1.2mm × 10m	9rls/box	04
75	300mm × 1.2mm × 10m	6rls/box	05


BC PETRO PASTE

IMPA Code	Sizes (W×T×L)	Packings	ISSA Code
81 24 81	3kg/can	3cans/box	75 551 01
BC PETRO	MASTIC	70.	
81 24 83	0.88kg/bar	25bars/box	75 551 02
PVC FIRM	TAPE		
	50mm × 0.2mm × 30m 100mm × 0.2mm × 30m 150mm × 0.2mm × 30m	66rls/box 33rls/box 22rls/box	Yellow, Red, Green, Gray



Application Instruction

- **a.** Remove moisture, oil, dust & scale, etc. on the surface by rag, chipper & scraper.
- **b.** Thinly coat with BC Petro Paste (0.3kg/m²)
- **c.** Stuff BC Petro Mastic on uneven areas-flanges, valves, cavities, & etc.
- **d.** Wrap BC Petro with enough tension to assure conformility to the surface.
- e. PVC Firm Tape is recommended for the prevention of wrapped BC Petro Tape from mechanical damages and for the good appearance of the wrapped items.





BC TAECHANG INDUSTRIAL CORP.