



DieselPower CFPP

Product Group: 650

Product number: 778405

General description

Unitor DieselPower CFPP is a product that can help to improve the cold flow properties of a marine distillate fuel. Unitor DieselPower CFPP will help reduce the wax formation and also to reduce the risk of wax fallout and accumulation.

Features

- Cold flow improver and pour point depressant
- Delays the onset of paraffin crystallization to improve cold flow properties

Benefits

- Enables you to handle the fuel at lower temperatures
- Adds safety in handling of the fuel by reducing the pour point of the fuel
- Keep the wax crystals in suspension preventing wax fallout and accumulation

A distillate fuel paraffin's. The paraffin's are quite large molecules and have a tendency to come together and form larger structures as the temperature drops in the fuel. The paraffin's can also be referred to as wax and a fuel with high wax content will have a tendency to cause wax formation at higher temperatures. Once the wax particles has formed they are difficult to dissolve back into the fuel.



DieselPower CFPP

Ordering information

Product Number	Product name
778405	DIESELPower CFPP 25 LTR

Directions for use

Unitor DieselPower CFPP should be dosed to the fuel tank prior to filling. Recommended dosage is one liter to one thousand liter of fuel (1:1000 or 1000 ppm). In case of poor respons dosage can be increased to one liter to five hundred liter of fuel (1:500 or 2000 ppm)

Please note: The dosing temperature should always be at least 5°C above the measuered cloud point of the fuel.

Dosage of product	1 ton fuel bunkered	10 ton fuel bunkered	50 ton bunkered	100 ton bunkered
1000 ppm	Dose 1 ltr	Dose 10 ltr	Dose 50 ltr	Dose 100 ltr
2000 ppm	Dose 2 ltr	Dose 20 ltr	Dose 100 ltr	Dose 200 ltr

Documentation

- [DIESELPower CFPP 25 LTR](#)

Type	Document	Size
LR DieselPower CFPP Performance Certificate	PDF	198 KB

Further Technical Data

Form	Liquid
Colour	Slightly hazy
Density	0,895 kg/ltr
Flash Point	60C
Pour Point	-30C