



## H.P. Wash 25 I

---

**Product Group: 651**

**Product number: 571729**

### General description

Unitor™ H.P. Wash is an alkaline cleaner with detergents and surfactants which quickly dissolve grease and dirt deposits.

Unitor™ H.P. Wash is designed for use with high pressure cleaning machines such as Unitor™ High Pressure Cleaners.

Unitor™ H.P. Wash is suitable for most painted surfaces and dries leaving a good shine.

### Features

- Reformulated with improved cleaning properties
- Does not contain nonyl phenol ethoxylates or other estrogenic compounds
- Biodegradable cleaner
- Non-flammable
- Formulated for use with H.P. cleaning machines
- Rapid dispersal of a large range of oils and greases
- Low dose rates 0.5–5%
- Leaves a good shine on hard surfaces after cleaning
- H.P. Wash is suitable for hot or cold high pressure spray equipment
- Can be used for general cleaning in the engine room, outside paint work and on the deck
- Can be used on Ro/Ro vessel car decks, for removal of traffic film
- Can be used for cleaning of fish holds and process machinery onboard factory vessels
- Approved by Marinfloc AB for use in engine rooms
- Phosphate free

---

### Ordering information

**Product number**

571729

**Product name**

H.P. WASH 25 LTR

---

### Approvals

- This composition meets the criteria for not being harmful to the marine environment according to MARPOL Annex V and may be discharged into the sea when used to clean cargo holds and external surfaces on ships.

---

## Directions for use

### Dosing method

For high pressure cleaning, apply the cleaning agent in an even layer using low pressure. Allow solution to penetrate soil for about 3–5 minutes before washing off thoroughly with high pressure water.

The recommended dose rates for the application using low pressure side of the cleaning machine, is between 0.5–5% depending on amount and type of soil.

Unitor™ H.P. Wash can be used by conventional cleaning using brush, rag or spray at a dose rate of 5–20% in water depending on the soiling. Allow 5 minutes for penetration, then rinse off with water.

### Sampling and testing

Unitor™ H.P. Wash is suitable for most painted surfaces and dries leaving a good shine.

---

## Documentation

- [HP WASH 25 LTR](#)
- 

## Further Technical Data

Form	Liquid
Appearance	Yellow
Density	1,1
pH, in conc.	12
Non Compatible	In concentrated form, may react with aluminium, zinc, tin and their alloys. May swell natural and synthetic rubber.